

SAFETY DATA SHEET

Armor All® Shield Brake Dust Repellent for Wheels

According to Regulation (EC) No 1907/2006, Annex II, as amended.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Armor All® Shield Brake Dust Repellent for Wheels

Product number AA16300

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Automotive wheel protectant.

Uses advised againstNo specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Armored Auto UK Ltd

Unit 16, Rassau Industrial Estate

Ebbw Vale Gwent NP23 5SD

UK

Tel: +44 1495 350234 Fax: + 44 1495 350431

euregulatory@eu.spectrumbrands.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234

Monday - Thursday: 0830 - 1700

Friday: 0830 - 1530

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Aerosol 1 - H222, H229

Health hazards Not Classified

Environmental hazards Not Classified

Physicochemical Containers can burst violently or explode when heated, due to excessive pressure build-up.

When sprayed on a naked flame or any incandescent material the aerosol vapours can be

ignited.

2.2. Label elements

Pictogram



Signal word Danger

Armor All® Shield Brake Dust Repellent for Wheels

Hazard statements H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

Precautionary statements P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Petroleum gases, liquefied, sweetened

25 - <50%

Substance with National workplace exposure limits.

Classification

Flam. Gas 1 - H220 Press. Gas (Liq.) - H280

Decamethylcyclopentasiloxane

25 - <50%

CAS number: 541-02-6 EC number: 208-764-9

Substance of very high concern (SVHC).

Classification

Not Classified

1.3-butadiene <0.025%

CAS number: 106-99-0 EC number: 203-450-8

Classification

Flam. Gas 1 - H220 Press. Gas (Liq.) - H280 Muta. 1B - H340

Carc. 1A - H350

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention if any discomfort continues. Show this Safety Data Sheet to the medical

personnel.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. Loosen tight clothing such as collar, tie or belt. Get medical attention if symptoms

are severe or persist.

Armor All® Shield Brake Dust Repellent for Wheels

Ingestion Rinse mouth thoroughly with water. Move affected person to fresh air and keep warm and at

rest in a position comfortable for breathing. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not

enter the lungs. Get medical attention if any discomfort continues.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Continue to

rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after

washing.

Eye contact Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do.

Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Spray/mists may cause respiratory tract irritation.

Ingestion Due to the physical nature of this product, exposure by this route is unlikely.

Skin contact Repeated exposure may cause skin dryness or cracking.

Eye contact May be slightly irritating to eyes. May cause discomfort.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically. Keep affected person under observation.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-

extinguishing media suitable for the surrounding fire.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Containers can burst violently or explode when heated, due to excessive pressure build-up.

Bursting aerosol containers may be propelled from a fire at high speed. If aerosol cans are ruptured, care should be taken due to the rapid escape of the pressurised contents and

propellant. Vapours may form explosive mixtures with air.

Hazardous combustion

products

Thermal decomposition or combustion products may include the following substances: Oxides

of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment

for firefighters

Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing conforming to European standard EN469 (including helmets, protective boots and gloves) will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Evacuate area.

No smoking, sparks, flames or other sources of ignition near spillage. Risk of explosion.

Armor All® Shield Brake Dust Repellent for Wheels

For non-emergency personnel No action shall be taken without appropriate training or involving any personal risk.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking,

sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Ventilate closed spaces before entering them. Use only non-sparking tools. Containers with collected spillage must be properly

labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section

13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Keep away from heat, sparks and open

flame. Provide adequate ventilation. Ground/bond container and receiving equipment. Keep

away from heat, sparks and open flame.

Advice on general occupational hygiene

Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take

precautionary measures against static discharges.

Storage class Flammable compressed gas storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

Petroleum gases, liquefied, sweetened

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³ Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

1,3-butadiene

Long-term exposure limit (8-hour TWA): WEL 10 ppm 22 mg/m³

Carc

WEL = Workplace Exposure Limit

Carc = Capable of causing cancer and/or heritable genetic damage.

8.2. Exposure controls

Protective equipment





Armor All® Shield Brake Dust Repellent for Wheels

Appropriate engineering

controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and

lighting equipment.

Eye/face protection Eyewear complying with an approved standard should be worn if a risk assessment indicates

eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles

or face shield.

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be worn if

a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.

Other skin and body

protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

Hygiene measuresDo not smoke in work area. Wash promptly with soap and water if skin becomes

contaminated. Wash at the end of each work shift and before eating, smoking and using the

toilet.

Respiratory protection Respiratory protection complying with an approved standard should be worn if a risk

assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective

equipment is suitable for its intended use and is 'CE'-marked.

Environmental exposure

controls

Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Aerosol.

Colour Colourless.

Odour Solvent.

Odour threshold Not determined.

pH Not determined.

Melting point Not relevant.

Initial boiling point and range Not relevant.

Evaporation rate Not determined.

Evaporation factor Not determined.

Flammability (solid, gas) Not determined.

Upper/lower flammability or

explosive limits

Not determined.

Vapour pressure Not determined.

Vapour density Not determined.

Relative density 0.957 @ 22.8°C Liquid.

Bulk density 787 kg/m³

Partition coefficient Not determined.

Auto-ignition temperature Not relevant.

Armor All® Shield Brake Dust Repellent for Wheels

Decomposition Temperature Not relevant.

Viscosity ~ 1 cP @ 20°C Liquid.

Explosive properties Not considered to be explosive.

Oxidising properties The mixture itself has not been tested but none of the ingredient substances meet the criteria

for classification as oxidising.

9.2. Other information

Other information No information required.

SECTION 10: Stability and reactivity

10.1. Reactivity

ReactivityThere are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stable at normal ambient temperatures and when used as recommended. Stable under the

prescribed storage conditions.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid exposing aerosol containers to high temperatures or direct sunlight. Avoid heat, flames

and other sources of ignition. Avoid the accumulation of vapours in low or confined areas.

Pressurised container: may burst if heated

10.5. Incompatible materials

Materials to avoid

No specific material or group of materials is likely to react with the product to produce a

hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Does not decompose when used and stored as recommended. Decomposition at ambient temperatures may generate the following substances: Carbon dioxide (CO2). Carbon

monoxide (CO). Acrid smoke or fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC50) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritationBased on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Armor All® Shield Brake Dust Repellent for Wheels

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met. Carcinogenicity

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not anticipated to present an aspiration hazard, based on chemical structure.

Toxicological information on ingredients.

Petroleum gases, liquefied, sweetened

Germ cell mutagenicity

Genotoxicity - in vitro Chromosome aberration: Negative. REACH dossier information.

Genotoxicity - in vivo Chromosome aberration: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity -

fertility

Screening - NOAEC 10000 ppm, Inhalation, Rat P, F1 REACH dossier information.

Reproductive toxicity development

Developmental toxicity: - NOAEC: 10426 ppm, Inhalation, Rat REACH dossier

information.

1,3-butadiene

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Positive. REACH dossier information. Muta. 1B - H340

Genotoxicity - in vivo Chromosome aberration: Positive. REACH dossier information.

Carcinogenicity

Carcinogenicity Known carcinogen based on animal evidence.

IARC carcinogenicity IARC Group 1 Carcinogenic to humans.

Reproductive toxicity

Reproductive toxicity -

Screening - NOAEC 6000 ppm, Inhalation, Rat P REACH dossier information.

fertility

Reproductive toxicity -

development

Developmental toxicity: - NOEC: 1000 ppm, Inhalation, Rat REACH dossier

information.

Armor All® Shield Brake Dust Repellent for Wheels

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEC 6.25 ppm, Inhalation, Mouse REACH dossier information.

SECTION 12: Ecological information

12.1. Toxicity

Toxicity Not considered toxic to fish. However, large or frequent spills may have hazardous effects on

the environment.

Ecological information on ingredients.

Petroleum gases, liquefied, sweetened

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 147.54 hours: 27.98 mg/l, Fish

REACH dossier information.

QSAR

Acute toxicity - aquatic

invertebrates

LC₅₀, 16.33 hours: 14.22 mg/l, Daphnia sp.

REACH dossier information.

QSAR

Acute toxicity - aquatic

plants

EC₅₀, 11.89 hours: 7.71 mg/l, Algae

REACH dossier information.

QSAR

1,3-butadiene

Acute aquatic toxicity

Acute toxicity - fish LC₅o, 96 hours: 45 mg/l, Pimephales promelas (Fat-head Minnow)

REACH dossier information.

QSAR

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 33 mg/l, Daphnia magna

REACH dossier information.

QSAR

Acute toxicity - aquatic

EC₅o, 72 hours: 33 mg/l, Freshwater algae

plants

REACH dossier information.

QSAR

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

Petroleum gases, liquefied, sweetened

Phototransformation Water - DT₅₀ : 1906 days

REACH dossier information.

Biodegradation Water - Degradation (100%): 385.5 hours

REACH dossier information.

The substance is readily biodegradable.

1,3-butadiene

Armor All® Shield Brake Dust Repellent for Wheels

Phototransformation Water - DT₅₀: 0.24 days

REACH dossier information.

Estimated value.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Petroleum gases, liquefied, sweetened

Partition coefficient log Pow: 2.3058 REACH dossier information. QSAR

1,3-butadiene

Partition coefficient log Pow: 1.99 REACH dossier information.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

Ecological information on ingredients.

1,3-butadiene

Henry's law constant 7900 Pa m³/mol @ 25°C REACH dossier information. QSAR

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

This product does not contain any substances classified as PBT or vPvB.

assessment

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations Do not

puncture or incinerate, even when empty.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name

AEROSOLS

(ADR/RID)

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Armor All® Shield Brake Dust Repellent for Wheels

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH) (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Council Directive of 20 May 1975 on the approximation of the laws of the Member States

relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Armor All® Shield Brake Dust Repellent for Wheels

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by

RID: European Agreement concerning the International Carriage of Dangerous Goods by

IMDG: International Maritime Dangerous Goods. IATA: International Air Transport Association.

ADN: European Agreement concerning the International Carriage of Dangerous Goods by

Inland Waterways.

ATE: Acute Toxicity Estimate. DNEL: Derived No Effect Level.

LC₅o: Lethal Concentration to 50 % of a test population.

LD₅o: Lethal Dose to 50% of a test population (Median Lethal Dose).

PBT: Persistent, Bioaccumulative and Toxic substance. vPvB: Very Persistent and Very Bioaccumulative.

BCF: Bioconcentration Factor.

Classification procedures according to Regulation (EC)

Aerosol 1 - H222, H229: Expert judgement.

1272/2008

Revision comments Section 3: Composition/information on ingredients // 3.2 Mixtures.

Revision date 04/07/2018

Revision 7

Supersedes date 20/04/2017

SDS number 401

Hazard statements in full H220 Extremely flammable gas.

H222 Extremely flammable aerosol.

H229 Pressurised container: may burst if heated.

H280 Contains gas under pressure; may explode if heated.

H340 May cause genetic defects.

H350 May cause cancer.

The information supplied here is accurate to the best knowledge and belief of Armored Auto UK Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Armored Auto UK Ltd assumes any legal responsibility. Any information or advice obtained from Armored Auto UK Ltd other than by means of this publication, and whether relating to Armored Auto UK Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Armored Auto UK Ltd when used instead of, or in conjunction with materials supplied by Armored Auto UK Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Armored Auto UK Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.