



Prestone



## SAFETY DATA SHEET

### Cockpit Satin New Car - Aerosol

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

##### 1.1. Product identifier

<b>Product name</b>	Cockpit Satin New Car - Aerosol
<b>Product number</b>	72072350031, 72072350022, 72072353001, SIM45, 52072360001, SAPP0601A, HAPP3701A, HAPP2501A, HAPP2801A, SAPP0026A, SAPP0078A, SAPP0078B
<b>REACH registration notes</b>	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

##### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Identified uses</b>	Dashboard Cleaner / Nettoyant plastiques
------------------------	--

##### 1.3. Details of the supplier of the safety data sheet

<b>Supplier</b>	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
<b>Contact person</b>	Contact Email address: info@holtsauto.com

##### 1.4. Emergency telephone number

<b>Emergency telephone</b>	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167
<b>National emergency telephone number</b>	<a href="http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks">http://echa.europa.eu/en/web/guest/support/helpdesks/national-helpdesks/list-of-national-helpdesks</a>

#### SECTION 2: Hazards identification

##### 2.1. Classification of the substance or mixture

###### Classification (EC 1272/2008)

<b>Physical hazards</b>	Aerosol 1 - H222, H229
<b>Health hazards</b>	Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H336
<b>Environmental hazards</b>	Aquatic Chronic 3 - H412


**Classification (67/548/EEC or 1999/45/EC)** Xi;R38. F+;R12. R52/53,R67.

<b>Human health</b>	Gas or vapour in high concentrations may irritate the respiratory system.
<b>Physicochemical</b>	The product is extremely flammable. Closed containers can burst violently when heated, due to excess pressure build-up.

## Cockpit Satin New Car - Aerosol

### 2.2. Label elements

#### Pictogram



#### Signal word

Danger

#### Hazard statements

H315 Causes skin irritation.  
 H319 Causes serious eye irritation.  
 H336 May cause drowsiness or dizziness.  
 H412 Harmful to aquatic life with long lasting effects.  
 H222 Extremely flammable aerosol.  
 H229 Pressurised container: may burst if heated

#### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P211 Do not spray on an open flame or other ignition source.  
 P251 Do not pierce or burn, even after use.  
 P261 Avoid breathing vapour/ spray.  
 P264 Wash contaminated skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P302+P352 IF ON SKIN: Wash with plenty of water.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312 Call a POISON CENTER/ doctor if you feel unwell.  
 P321 Specific treatment (see medical advice on this label).  
 P332+P313 If skin irritation occurs: Get medical advice/ attention.  
 P337+P313 If eye irritation persists: Get medical advice/ attention.  
 P362+P364 Take off contaminated clothing and wash it before reuse.  
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
 P405 Store locked up.  
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P102 Keep out of reach of children.  
 P101 If medical advice is needed, have product container or label at hand.  
 P501 Dispose of contents/ container in accordance with local regulations.

#### Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

#### Contains

Naphtha (petroleum), hydrotreated light, Naphtha (petroleum), hydrotreated heavy (<0.1% Benzene)

#### Detergent labelling

≥ 30% aliphatic hydrocarbons, 5 - < 15% non-ionic surfactants, < 5% perfumes

### 2.3. Other hazards

#### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

## Cockpit Satin New Car - Aerosol

<b>BUTANE</b>		<b>10-30%</b>
CAS number: 106-97-8		EC number: 203-448-7
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		
<b>Naphtha (petroleum), hydrotreated light</b>		<b>10-30%</b>
CAS number: 64742-49-0		EC number: 265-151-9
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 2 - H225	Xn;R65. Xi;R38. F;R11. N;R51/53. R67.	
Skin Irrit. 2 - H315		
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		
<b>Naphtha (petroleum), hydrotreated heavy (&lt;0.1% Benzene)</b>		<b>10-30%</b>
CAS number: 64742-48-9		EC number: 265-150-3
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Liq. 3 - H226	Xn;R65. R10,R66,R67.	
STOT SE 3 - H336		
Asp. Tox. 1 - H304		
<b>ISOBUTANE</b>		<b>10-30%</b>
CAS number: 75-28-5		EC number: 200-857-2
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Flam. Gas 1 - H220	F+;R12	
Press. Gas		
<b>Alcohols, C12-13, ethoxylated</b>		<b>1-5%</b>
CAS number: 66455-14-9		EC number: 500-165-3
M factor (Acute) = 1		
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Eye Dam. 1 - H318	Xi;R41. N;R50.	
Aquatic Acute 1 - H400		
<b>SOLVENT DEWAXED LIGHT PARAFFINIC DISTILLATE (PETROLEUM)</b>		<b>1-5%</b>
CAS number: 64742-55-8		EC number: 265-158-7
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>	
Asp. Tox. 1 - H304	Xn;R65.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

## Cockpit Satin New Car - Aerosol

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>Inhalation</b>	Keep affected person away from heat, sparks and flames. Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Keep affected person warm and at rest. Get medical attention immediately.
<b>Ingestion</b>	Not relevant.
<b>Skin contact</b>	Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.
<b>Eye contact</b>	If liquid has entered the eyes, proceed as follows. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.3. Indication of any immediate medical attention and special treatment needed

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

**Suitable extinguishing media** Extinguish with the following media: Powder. Dry chemicals, sand, dolomite etc. Water spray, fog or mist.

#### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Risk of explosion if heated. Containers can burst violently or explode when heated, due to excessive pressure build-up.

#### 5.3. Advice for firefighters

**Protective actions during firefighting** Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.2. Environmental precautions

#### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet.

#### 6.4. Reference to other sections

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

**Usage precautions** Keep away from heat, sparks and open flame. Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level.

#### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

**Storage class** Flammable compressed gas storage.

#### 7.3. Specific end use(s)

## Cockpit Satin New Car - Aerosol

### SECTION 8: Exposure Controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limits

##### BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m<sup>3</sup>

##### ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

WEL = Workplace Exposure Limit

**Ingredient comments** WEL = Workplace Exposure Limits

#### Oleic Acid (CAS: 112-80-1)

**Ingredient comments** WEL = Workplace Exposure Limits

#### 8.2. Exposure controls

##### Protective equipment



##### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

##### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

##### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Rubber (natural, latex). EN374

##### Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

##### Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Do not smoke in work area. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. When using do not eat, drink or smoke.

##### Respiratory protection

No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Aerosol.
<b>Odour</b>	New Car
<b>Flash point</b>	< 0°C CC (Closed cup).

#### 9.2. Other information

**Volatile organic compound** This product contains a maximum VOC content of 95 %.

## Cockpit Satin New Car - Aerosol

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

#### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures.

#### 10.3. Possibility of hazardous reactions

#### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition. Avoid contact with the following materials: Strong oxidising agents. Strong alkalis. Strong mineral acids.

#### 10.5. Incompatible materials

#### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire creates: Vapours/gases/fumes of: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

**Inhalation** Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations. May cause eye and respiratory system irritation. Symptoms following overexposure may include the following: Headache. Vapours may cause headache, fatigue, dizziness and nausea.

**Ingestion** No harmful effects expected from quantities likely to be ingested by accident.

**Skin contact** Prolonged and frequent contact may cause redness and irritation.

**Eye contact** Vapour or spray in the eyes may cause irritation and smarting.

### SECTION 12: Ecological Information

**Ecotoxicity** The product is not expected to be hazardous to the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

#### 12.1. Toxicity

#### 12.2. Persistence and degradability

#### 12.3. Bioaccumulative potential

#### 12.4. Mobility in soil

#### 12.5. Results of PBT and vPvB assessment

#### 12.6. Other adverse effects

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

**Disposal methods** Empty containers must not be punctured or incinerated because of the risk of an explosion. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** WGK : 2 (Germany)

### SECTION 14: Transport information

#### 14.1. UN number

## Cockpit Satin New Car - Aerosol

UN No. (ADR/RID)	1950
UN No. (IMDG)	1950
UN No. (ICAO)	1950
UN No. (ADN)	1950

### 14.2. UN proper shipping name

Proper shipping name (ADR/RID)	AEROSOLS
Proper shipping name (IMDG)	AEROSOLS
Proper shipping name (ICAO)	AEROSOLS
Proper shipping name (ADN)	AEROSOLS

### 14.3. Transport hazard class(es)

ADR/RID class	2.1
ADR/RID classification code	5F
ADR/RID label	2.1
IMDG class	2.1
ICAO class/division	2.1
ADN class	2.1

#### Transport labels



### 14.4. Packing group

ADR/RID packing group	None
IMDG packing group	None
ADN packing group	None
ICAO packing group	None

### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant  
No.

### 14.6. Special precautions for user

EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to  
Annex II of MARPOL 73/78  
and the IBC Code  
Not applicable.

## SECTION 15: Regulatory information

## Cockpit Satin New Car - Aerosol

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

<b>National regulations</b>	The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).
<b>EU legislation</b>	Dangerous Substances Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EC. Detergents Regulation EC 648/2004 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

### 15.2. Chemical safety assessment

#### SECTION 16: Other information

<b>Revision date</b>	12/08/2015
<b>Revision</b>	19
<b>Supersedes date</b>	12/04/2014
<b>SDS number</b>	13610
<b>Risk phrases in full</b>	Not classified. R10 Flammable. R11 Highly flammable. R12 Extremely flammable. R38 Irritating to skin. R41 Risk of serious damage to eyes. R50 Very toxic to aquatic organisms. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness.
<b>Hazard statements in full</b>	H220 Extremely flammable gas. H222 Extremely flammable aerosol. H225 Highly flammable liquid and vapour. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H318 Causes serious eye damage. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H400 Very toxic to aquatic life. H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.