Safety Data Sheet



SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Havoline Super 2T-X

Product Number(s): 804040

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Uses: 2T Engine Oil

1.3 Details of the supplier of the safety data sheet

Chevron Products UK Limited 1 Westferry Circus Canary Wharf London E14 4HA United Kingdom

email: eumsds@chevron.com

1.4 Emergency telephone number

Transportation Emergency Response

Europe: 0044/(0)18 65 407333

Health Emergency

Europe: 0044/(0)18 65 407333

Product Information

Product Information: FAX number: 0044/20 77 19 5171

SECTION 2 HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

CLP CLASSIFICATION: Target organ toxicant (central nervous system): Category 3, H336.

2.2 Label elements

Under the criteria of Regulation (EC) No 1272/2008 (CLP):

Revision Number: 0 1 of 11 Havoline Super 2T-X MSDS: 41534



Signal Word: Warning

HAZARD STATEMENTS:

Health Hazards: May cause drowsiness or dizziness (H336).

- contains: Distillates (petroleum), hydrotreated light

Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium

salts. May produce an allergic reaction.

PRECAUTIONARY STATEMENTS:

General: Keep out of reach of children (P102). If medical advice is needed, have product container or

label at hand (P101).

Prevention: Use only outdoors or in a well-ventilated area (P271).

Response: Call a POISON CENTER or doctor/physician if you feel unwell (P312).

Storage: Store locked up (P405).

Disposal: Dispose of contents/container in accordance with applicable local/regional/national/international

regulations (P501).

Supplemental Hazard Information (EU): Repeated exposure may cause skin dryness or cracking (EUH066).

2.3 Other hazards

This product is not, or does not contain, a substance that is a potential PBT or a vPvB.

SECTION 3 COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

This material is a mixture.

COMPONENTS	CAS	EC	REGISTRATION	CLP	AMOUNT
	NUMBER	NUMBER	NUMBER	CLASSIFICATION	
Highly refined mineral oil (C15 - C50)	Mixture	*	***		40 - 69 %weight
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8	**		10 - 30 %weight
Amines, polyethylenepoly-,	84605-20-9	617-593-2		Aquatic Chronic 4/H413	1 - 5 %weight

Revision Number: 0 2 of 11 Havoline Super 2T-X MSDS: 41534

reaction products with succinic anhydride polyisobutenyl derivs.				
Benzenesulfonic acid, methyl-, mono-C20-24-branched alkyl derivs., calcium salts	722503-68-6	Not applicable	Aquatic Chronic 4/H413; Skin Sens. 1/H317	0.1 - < 1 %weight

The full text of all CLP H-statements is shown in Section 16.

SECTION 4 FIRST AID MEASURES

4.1 Description of first aid measures

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water.

Skin: Wash skin with water immediately and remove contaminated clothing and shoes. Get medical attention if any symptoms develop. To remove the material from skin, apply a waterless hand cleaner, mineral oil, or petroleum jelly. Then wash with soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse.

Ingestion: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: Move the exposed person to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention if breathing difficulties continue.

4.2 Most important symptoms and effects, both acute and delayed IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

Eye: Not expected to cause prolonged or significant eye irritation.

Skin: Skin contact may cause drying or defatting of the skin. Symptoms may include pain, itching, discoloration, swelling, and blistering.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: Contains a petroleum-based mineral oil. May cause respiratory irritation or other pulmonary effects following prolonged or repeated inhalation of oil mist at airborne levels above the recommended mineral oil mist exposure limit. Symptoms of respiratory irritation may include coughing and difficulty

Revision Number: 0 3 of 11 Havoline Super 2T-X MSDS: 41534

^{*}Contains one or more of the following EINECS numbers: 265-090-8, 265-091-3, 265-096-0, 265-097-6, 265-098-1, 265-101-6, 265-155-0, 265-156-6, 265-157-1, 265-158-7, 265-159-2, 265-160-8, 265-161-3, 265-166-0, 265-169-7, 265-176-5, 276-735-8, 276-736-3, 276-737-9, 276-738-4, 278-012-2.

^{**}Not available or substance is not currently required for registration under REACH.

^{***} Contains one or more of the following REACH registration numbers: 01-2119488706-23,

⁰¹⁻²¹¹⁹⁴⁸⁷⁰⁶⁷⁻³⁰, 01-2119487081-40, 01-2119483621-38, 01-2119480374-36, 01-2119488707-21,

^{01-2119467170-45, 01-2119480375-34, 01-2119484627-25, 01-2119480132-48, 01-2119487077-29,}

 $^{01-2119489287-22,\, 01-2119480472-38,\, 01-2119471299-27,\, 01-2119485040-48,\, 01-2119555262-43,\, 01-2119489287-22,\, 01-2119480472-38,\, 01-2119471299-27,\, 01-2119485040-48,\, 01-2119555262-43,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-2119489287-22,\, 01-211948928-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-2119488-22,\, 01-211948-22,\, 01-2}$

^{01-2119495601-36, 01-2119474889-13, 01-2119474878-16.}

breathing. Excessive or prolonged breathing of this material may cause central nervous system effects. Central nervous system effects may include headache, dizziness, nausea, vomiting, weakness, loss of coordination, blurred vision, drowsiness, confusion, or disorientation. At extreme exposures, central nervous system effects may include respiratory depression, tremors or convulsions, loss of consciousness, coma or death.

DELAYED OR OTHER SYMPTOMS AND HEALTH EFFECTS: Not classified.

4.3 Indication of any immediate medical attention and special treatment needed Not applicable.

SECTION 5 FIRE FIGHTING MEASURES

5.1 Extinguishing media

Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

5.2 Special hazards arising from the substance or mixture

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

5.3 Advice for firefighters

This material will burn although it is not easily ignited. See Section 7 for proper handling and storage. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Eliminate all sources of ignition in vicinity of spilled material. Refer to Sections 5 and 8 for more information.

6.2 Environmental precautions

Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater.

6.3 Methods and material for containment and cleaning up

Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil and dispose of in a manner consistent with applicable requirements. Place other contaminated materials in disposable containers and dispose of in a manner consistent with applicable requirements. Report spills to local authorities as appropriate or required.

6.4 Reference to other sections

See sections 8 and 13.

Revision Number: 0 4 of 11 Havoline Super 2T-X MSDS: 41534

SECTION 7 HANDLING AND STORAGE

7.1 Precautions for safe handling

General Handling Information: Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Wash thoroughly after handling.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

7.2 Conditions for safe storage, including any incompatibilitiesNot Applicable

7.3 Specific end use(s):2T Engine Oil

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances. Refer to appropriate CEN standards.

8.1 Control parameters

Occupational Exposure Limits:

Component	Country/ Agency	TWA	STEL	Ceiling	Notation
Highly refined mineral oil (C15 - C50)	United	5 mg/m3	10 mg/m3		
	Kingdom				

Consult local authorities for appropriate values.

8.2 Exposure controls

ENGINEERING CONTROLS:

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels

Revision Number: 0 5 of 11 **Havoline Super 2T-X MSDS**: 41534

below the recommended exposure limits. Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice.

Skin Protection: Wear protective clothing to prevent skin contact. Selection of protective clothing may include gloves, apron, boots, and complete facial protection depending on operations conducted. Suggested materials for protective gloves include: Neoprene, Nitrile Rubber.

Respiratory Protection: Determine if airborne concentrations are below the recommended occupational exposure limits for jurisdiction of use. If airborne concentrations are above the acceptable limits, wear an approved respirator that provides adequate protection from this material, such as: Air-Purifying Respirator for Organic Vapors. If user operations generate an oil mist, determine if airborne concentrations are below the occupational exposure limit for mineral oil mist. If not, wear an approved respirator that provides adequate protection from the measured concentrations of this material. For air-purifying respirators use a particulate cartridge. Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

ENVIRONMENTAL EXPOSURE CONTROLS:

See relevant Community environmental protection legislation or the Annex, as applicable.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Attention: the data below are typical values and do not constitute a specification.

9.1 Information on basic physical and chemical properties

Appearance Color: Blue

Physical State: Liquid Odor: Petroleum odor

Odor Threshold: No data available

pH: Not Applicable

Melting Point: No data available **Freezing Point**: No data available

Initial Boiling Point: >315°C (599°F) Minimum

Flashpoint: (Cleveland Open Cup) > 100 °C (> 212 °F) Minimum

Evaporation Rate: No data available

Flammability (solid, gas): No Data Available

Flammability (Explosive) Limits (% by volume in air):

Lower: Not Applicable Upper: Not Applicable

Vapor Pressure: <0.01 mmHg Maximum @ 37.8 °C (100 °F)

Vapor Density (Air = 1): >1 Minimum

Relative Density: 0.8680 kg/l (Typical) @ 15°C (59°F)

Density: 0.87 kg/l @ 15°C (59°F) (Typical)

Solubility: Soluble in hydrocarbons; insoluble in water **Partition coefficient: n-octanol/water:** No data available

Auto-ignition temperature: No data available

Revision Number: 0 6 of 11 Havoline Super 2T-X MSDS: 41534

Decomposition temperature: No data available **Viscosity:** 53.40 mm2/s @ 40°C (104°F) Minimum

Explosive Properties: No Data Available **Oxidising properties:** No Data Available

9.2 Other Information: No Data Available

SECTION 10 STABILITY AND REACTIVITY

- **10.1 Reactivity:** May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
- **10.2 Chemical Stability:** This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
- 10.3 Possibility of hazardous reactions: Hazardous polymerization will not occur.
- 10.4 Conditions to Avoid: Not applicable
- 10.5 Incompatible materials to avoid: Not applicable
- **10.6 Hazardous decomposition products:** None known (None expected)

SECTION 11 TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Serious Eye Damage/Irritation: The eye irritation hazard is based on evaluation of data for product components.

Skin Corrosion/Irritation: The skin irritation hazard is based on evaluation of data for product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for product components.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate (dermal): Not Applicable

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate (oral): Not Applicable

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for product components.

Acute Toxicity Estimate (inhalation): Not Applicable

Germ Cell Mutagenicity: The hazard evaluation is based on data for components or a similar material.

Carcinogenicity: The hazard evaluation is based on data for components or a similar material.

Reproductive Toxicity: The hazard evaluation is based on data for components or a similar material.

Revision Number: 0 7 of 11 **Havoline Super 2T-X MSDS:** 41534

Specific Target Organ Toxicity - Single Exposure: The hazard evaluation is based on data for components or a similar material.

Specific Target Organ Toxicity - Repeated Exposure: The hazard evaluation is based on data for components or a similar material.

Aspiration Toxicity: No data available

ADDITIONAL TOXICOLOGY INFORMATION:

In accordance with the Directive 94/69/EC (21st ATP to DSD), Nota L, reference IP 346/92: "DMSO Extraction Method", we have determined that the base oils used in this preparation are not carcinogenic. During use in engines, contamination of oil with low levels of cancer-causing combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water.

SECTION 12 ECOLOGICAL INFORMATION

12.1 Toxicity

This material is not expected to be harmful to aquatic organisms. The product has not been tested. The statement has been derived from the properties of the individual components.

12.2 Persistence and degradability

This material is not expected to be readily biodegradable. The product has not been tested. The statement has been derived from the properties of the individual components.

12.3 Bioaccumulative potential

Bioconcentration Factor: No Data Available

Octanol/Water Partition Coefficient: No data available

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

This product is not, or does not contain, a substance that is a potential PBT or a vPvB.

12.6 Other adverse effects

No other adverse effects identified.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Use material for its intended purpose or recycle if possible. Oil collection services are available for used oil

Revision Number: 0 8 of 11 Havoline Super 2T-X MSDS: 41534

recycling or disposal. Place contaminated materials in containers and dispose of in a manner consistent with applicable regulations. Contact your sales representative or local environmental or health authorities for approved disposal or recycling methods.

SECTION 14 TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult appropriate Dangerous Goods Regulations for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

ADR/RID

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN number: Not applicable

14.2 UN proper shipping name: Not applicable **14.3 Transport hazard class(es)**: Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

ICAO

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN number: Not applicable

14.2 UN proper shipping name: Not applicable **14.3 Transport hazard class(es):** Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

IMO

NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT

14.1 UN number: Not applicable

14.2 UN proper shipping name: Not applicable14.3 Transport hazard class(es): Not applicable

14.4 Packing group: Not applicable

14.5 Environmental hazards: Not applicable14.6 Special precautions for user: Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code: Not applicable

SECTION 15 REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Revision Number: 0 9 of 11 Havoline Super 2T-X MSDS: 41534

REGULATORY LISTS SEARCHED:

01=EU Directive 76/769/EEC: Restrictions on the marketing and use of certain dangerous substances.

02=EU Directive 90/394/EEC: Carcinogens at work.

03=EU Directive 92/85/EEC: Pregnant or breastfeeding workers.

04=EU Directive 96/82/EC (Seveso II): Article 9.

05=EU Directive 96/82/EC (Seveso II): Articles 6 and 7.

06=EU Directive 98/24/EC: Chemical agents at work.

07=EU Directive 2004/37/EC: On the protection of workers.

08=EU Regulation EC No. 689/2008: Annex 1, Part 1.

09=EU Regulation EC No. 689/2008: Annex 1, Part 2.

10=EU Regulation EC No. 689/2008: Annex 1, Part 3.

11=EU Regulation EC No. 850/2004: Prohibiting and restricting persistent organic pollutants (POPs).

12=EU REACH, Annex XVII: Restrictions on manufacture, placing on the market and use of certain dangerous substances, mixture & article.

13=EU REACH, Annex XIV: Candidate List of Substances of Very High Concern for Authorization (SVHC).

No components of this material were found on the regulatory lists above.

CHEMICAL INVENTORIES:

All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), KECI (Korea), PICCS (Philippines), TSCA (United States).

One or more components does not comply with the following chemical inventory requirements: IECSC (China).

15.2 Chemical safety assessment

No chemical safety assessment.

SECTION 16 OTHER INFORMATION

REVISION STATEMENT: This is a new Material Safety Data Sheet.

Revision Date: APRIL 06, 2016

Full text of CLP H-statements:

H304; May be fatal if swallowed and enters airways

H413; May cause long lasting harmful effects to aquatic life

H317; May cause allergic skin reaction

H336; May cause drowsiness or dizziness

ABBREVIATIONS THAT MAY HAVE BEEN USED IN THIS DOCUMENT:

TLV - Threshold Limit Value	TWA - Time Weighted Average
STEL - Short-term Exposure Limit	PEL - Permissible Exposure Limit
CVX - Chevron	CAS - Chemical Abstract Service Number

Revision Number: 0 10 of 11 Havoline Super 2T-X MSDS: 41534

NQ - Not Quantifiable

Prepared according to the criteria of EU Regulation 1907/2006 by the Chevron Energy Technology Company, 100 Chevron Way, Richmond, California 94802.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

No Annex

Revision Number: 0 11 of 11 Havoline Super 2T-X MSDS: 41534