

SAFETY DATA SHEET

REF: CGP/TT15MR2/3594

1. IDENTIFIC			ATION AND TH			
	ATION OF THE SUBS	TANCE/PREPAR	ATION AND TH	E COM	PANY/UNDERTAKIN	G
Product name:		CAR GLASS POLISH				
Supplier:		AUTOGLYM, Works Road, Letchworth, England SG6 1LU				
Emergency telephone number:		44 (0) 1462 677766				
dentification	of the preparation:					
Product use:		glass cleaner				
Packing size:		100 & 325 ml				
2. COMPOSI	TION/INFORMATION C		S			
Chemical Nam	ie	C	CAS-No	С	lass	Weight %
Aliphatic hydrocarbon solvent (<25% arc		omatics) 6	4742-88-7	X	n; R65 R10, R51/53, R6	66 20 - 50
Anhydrous aluminium silicate		6	6402-68-4			1 - 5
3. HAZARDS	IDENTIFICATION					
nhalation:	May cause irritation of respiratory tract, Anaesthetic in high concentrations, may cause drowsiness, dizziness and affect the central nervous system.					
	May irritate. May cause	dermatitis.				
Eye contact:	-					
ngestion:	Liquid aspirated into lun	gs may cause bror	nchopneumonia o	r pulmoi	nary oedema.	
4. FIRST AID	MEASURES					
nhalation:	Move to fresh air. Obtai	n medical attention	l.			
Skin contact:	Wash off with soap and	water. Remove an	d wash contamina	ated clot	hing before re-use.	
Eye contact:	Flush with plenty of wat	er. If eye irritation p	persists, consult a	special	ist.	
ngestion:	Do not induce vomiting.	Consult a physicia	an.			
5. FIRE-FIGH	TING MEASURES					
Suitable extin	guishing media: foam,	carbon dioxide (CC	D2), dry chemical			
		DEC				
6. ACCIDEN	AL RELEASE MEASU	RE3				
	I precautions: Prevent p		ng drains			
Environmenta		product from enteri	•	rt absor	bent material.	
Environmenta Methods for c	I precautions: Prevent p	product from enteri	•	rt absor	bent material.	
Environmenta Methods for c 7. HANDLINC	I precautions: Prevent pleaning up: Remove all	product from enterin sources of ignition	. Soak up with ine		bent material.	
Environmenta Methods for cl 7. HANDLINC Handling: Do	I precautions: Prevent pleaning up: Remove all AND STORAGE	broduct from enterin sources of ignition st. Avoid contact wi	b. Soak up with ine		bent material.	
Environmenta Methods for cl 7. HANDLINC Handling: Do Storage: Ke	I precautions: Prevent p leaning up: Remove all G AND STORAGE	broduct from enterin sources of ignition st. Avoid contact wi ignition - No smok	th the skin and th		bent material.	
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR	I precautions: Prevent p leaning up: Remove all AND STORAGE o not breathe vapours/dus eep away from sources of E CONTROLS / PERS	broduct from enterin sources of ignition st. Avoid contact wi ignition - No smok	th the skin and th	e eyes.	bent material. tional exposure limits	
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam	I precautions: Prevent p leaning up: Remove all AND STORAGE o not breathe vapours/dus eep away from sources of E CONTROLS / PERS	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT	th the skin and th	e eyes.	tional exposure limits	
Environmenta Methods for c 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydro	I precautions: Prevent p leaning up: Remove all S AND STORAGE o not breathe vapours/dus eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% are	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT	th the skin and th ting. TON UK National LTEL=125pp	e eyes. occupa m (600m	tional exposure limits	
Environmenta Methods for c 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydro Anhydrous alur	I precautions: Prevent p leaning up: Remove all S AND STORAGE o not breathe vapours/dus eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% are	broduct from enterin sources of ignition et. Avoid contact wi i ignition - No smok ONAL PROTECT	th the skin and th ting. TON UK National LTEL=125pp LTEL=10mg/i	e eyes. occupa n (600m n ³ (TD),	tional exposure limits	
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydrou Anhydrous alur Engineering m Personal prote	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dust eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment:	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT omatics) ate ventilation, esp	th the skin and th ting. TON UK National LTEL=125pp LTEL=10mg/i	e eyes. occupa n (600m n ³ (TD),	tional exposure limits	
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydrou Anhydrous alur Engineering m Personal prote	I precautions: Prevent p leaning up: Remove all AND STORAGE o not breathe vapours/dus eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adequ	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT omatics) ate ventilation, esp	th the skin and th ting. TON UK National LTEL=125pp LTEL=10mg/i	e eyes. occupa n (600m n ³ (TD),	tional exposure limits	
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydro Anhydrous alur Engineering m Personal protectio	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dust eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment:	product from enterin sources of ignition st. Avoid contact wit ignition - No smok ONAL PROTECT omatics) ate ventilation, esp material gloves	th the skin and th ting. TON UK National LTEL=125pp LTEL=10mg/i	e eyes. occupa n (600m n ³ (TD),	tional exposure limits	:
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydro Anhydrous alur Engineering m Personal protection 9. PHYSICAL	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dus eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment: on: PVC or other plastic AND CHEMICAL PRO	product from enterin sources of ignition st. Avoid contact wit ignition - No smok ONAL PROTECT omatics) ate ventilation, esp material gloves	th the skin and th ting. ION UK National LTEL=125pp LTEL=10mg/i recially in confined	e eyes. occupa n (600m n ³ (TD),	tional exposure limits	
Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydrous Anhydrous alur Engineering m Personal protection 9. PHYSICAL Form: creat	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dus eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment: on: PVC or other plastic AND CHEMICAL PRO am	product from enterin sources of ignition st. Avoid contact wi i ignition - No smok ONAL PROTECT comatics) ate ventilation, esp material gloves DPERTIES	th the skin and th ting. ION UK National LTEL=125pp LTEL=10mg/i recially in confined	e eyes. occupa n (600r n ³ (TD), I areas.	tional exposure limits ng/m³) 5mg/m³ (RD) Flash point: 4	
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydro Anhydrous alur Engineering m Personal protectio 9. PHYSICAL Form: crea Colour: blue	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dust eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment: on: PVC or other plastic AND CHEMICAL PRO am B	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT omatics) ate ventilation, esp material gloves OPERTIES coiling point/range	th the skin and th ting. TION UK National LTEL=125pp LTEL=10mg/i recially in confined	e eyes. occupa n (600r n ³ (TD), I areas.	tional exposure limits ng/m³) 5mg/m³ (RD) Flash point: 4	5 ° (
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydro Anhydrous alur Engineering m Personal protection 9. PHYSICAL Form: creat Colour: blue pH: 10 -	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dust eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment: on: PVC or other plastic AND CHEMICAL PRO am B	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT omatics) ate ventilation, esp material gloves OPERTIES coiling point/range	th the skin and th ting. TION UK National LTEL=125pp LTEL=10mg/i recially in confined	e eyes. occupa n (600r n ³ (TD), I areas.	tional exposure limits ng/m³) 5mg/m³ (RD) Flash point: 4	5 ° C
Environmenta Methods for cl 7. HANDLING Handling: Do Storage: Ke 8. EXPOSUR Chemical Nam Aliphatic hydror Anhydrous alur Engineering m Personal protection 9. PHYSICAL Form: creat Colour: blue pH: 10 -	I precautions: Prevent pleaning up: Remove all AND STORAGE on to breathe vapours/dus eep away from sources of E CONTROLS / PERS ne: carbon solvent (<25% ard minium silicate neasures: Ensure adeque ection equipment: on: PVC or other plastic AND CHEMICAL PRO am B e D 11	oroduct from enterin sources of ignition st. Avoid contact wi ignition - No smok ONAL PROTECT omatics) ate ventilation, esp material gloves OPERTIES coiling point/range	th the skin and th ting. TION UK National LTEL=125pp LTEL=10mg/i recially in confined	e eyes. occupa n (600r n ³ (TD), I areas.	tional exposure limits ng/m³) 5mg/m³ (RD) Flash point: 4	5 ° C

CAR GLASS POLISH

11. TOXICOLOGICAL INFORMATION

Solvent: LD50/oral/rat = > 5 g/kg, LD50/dermal/rabbit = > 3 g/kg.

12. ECOLOGICAL INFORMATION

Solvent: N - Dangerous for the environment. Toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products Ensure confirmity to local disposal regulations

14. TRANSPORT INFORMATION

Conveyance classification: Not classified as dangerous in the meaning of transport regulations

15. REGULATORY INFORMATION

Classification according to European directive on classification of hazardous preparations 90/492/EEC

Contains: Petroleum distillates

R-phrase(s): R66 - Repeated exposure may cause skin dryness and cracking

S-phrase(s): S2 - Keep out of reach of children. S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

16. OTHER INFORMATION

Last revision dated: 18/03/98

Further information:

Changes made to sections: 15

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.