



# SAFETY DATA SHEET

Gulf Formula GX, SAE 5W-40

01113/5W-40/4

Issuing Date: 09-29-2016

Revision Date: 09-29-2016

Version 1

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Name **Gulf Formula GX, SAE 5W-40**  
Product Code(s): 01113/5W-40/4

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Engine oil  
Uses advised against Any other purpose.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Gulf Oil Supply Company Limited  
B2 Industry Street, Qormi, QRM 3000, Malta  
+44 207 321 6219  
products@gulfoilltd.com sds@gulfoilltd.com

### 1.4. Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276  
(+) 1 760 476 3961 Code 334276  
(+) 32 (0) 3241 33 55

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Contains Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate May produce an allergic reaction.

### 2.2. Label Elements

Signal Word  
None

#### Hazard Statements

EUH208 - Contains Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate May produce an allergic

reaction.

### 2.3. Other hazards

No information available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	25% - 50%	Asp. Tox. 1 (H304) (EUH066)	-
Polyolefin polyamine succinimide, polyol	-	NOT AVAILABLE	2.5% - 10%	Aquatic Chronic 4 (H413)	no data available
Phenol, 2,2'-polythiobis[4-C8-30-alkyl derivs., calcium salts, overbased	291-829-9	90480-91-4	1% - 2.5%	Aquatic Chronic 4 (H413)	01-2119524004-56-xxx x
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	272-028-3	68649-42-3	1% - 2.5%	Eye Dam. 1 (H318) Aquatic Chronic 2 (H411)	01-2119657973-23-xxx x
Calcium di(alkyl(C20-C24, even numbered) branched)-methyl benzenesulfonate	-	722503-68-6	0% - 1%	Skin Sens. 1 (H317) Aquatic Chronic 4 (H413)	no data available

### Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346.

See Section 15 for additional information on base oils.

\*\* Substances for which there are Community workplace exposure limits

**Full text of H- and EUH-phrases: see section 16**

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first-aid measures

#### General advice

May produce an allergic reaction. When symptoms persist or in all cases of doubt seek medical advice.

#### Inhalation

Move to fresh air.

#### Skin contact

Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing before re-use. May cause an allergic skin reaction. If symptoms persist, call a physician.

#### Eye contact

Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.

#### Ingestion

Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical advice.

---

**Protection of First-aiders** Use personal protective equipment. Avoid contact with skin, eyes and clothing.

#### **4.2. Most important symptoms and effects, both acute and delayed**

**Main Symptoms** May cause allergic skin reaction

#### **4.3. Indication of immediate medical attention and special treatment needed**

**Notes to physician** May cause sensitization of susceptible persons. Treat symptomatically.

### **SECTION 5: FIRE FIGHTING MEASURES**

#### **5.1. Extinguishing media**

##### **Suitable Extinguishing Media**

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.; Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

##### **Extinguishing media which shall not be used for safety reasons**

Do not use a solid water stream as it may scatter and spread fire

#### **5.2. Special hazards arising from the substance or mixture**

##### **Special Hazard**

In the event of fire and/or explosion do not breathe fumes. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Thermal decomposition can lead to release of irritating gases and vapors. This material creates a fire hazard because it floats on water.

##### **Hazardous Decomposition Products**

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

#### **5.3. Advice for firefighters**

##### **Special protective equipment for fire-fighters**

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

### **SECTION 6: ACCIDENTAL RELEASE MEASURES**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Ensure adequate ventilation. Use personal protective equipment. Avoid contact with skin, eyes and clothing.

**Advice for non-emergency personnel** Material can create slippery conditions.

**Advice for emergency responders** For personal protection see section 8.

#### **6.2. Environmental precautions**

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

#### **6.3. Methods and materials for containment and cleaning up**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

#### 6.4. Reference to other sections

See Section 8/12/13 for additional information

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

#### Incompatible Materials

Oxidizing agents

### 7.3. Specific end uses

Engine oil

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain
Highly refined base oil (Viscosity >20.5 cSt @40°C)				VLA-EC: 10 mg/m <sup>3</sup> VLA-ED: 5 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				VLA-EC: 10 mg/m <sup>3</sup> VLA-ED: 5 mg/m <sup>3</sup>

Chemical Name	Germany	Italy	Portugal	The Netherlands
Highly refined base oil (Viscosity >20.5 cSt @40°C)		TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)		TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>

Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (Mist)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>	STEL: 10 mg/m <sup>3</sup> TWA: 5 mg/m <sup>3</sup> (Mist)

Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m <sup>3</sup> (Öljysumu)	TWA: 1 mg/m <sup>3</sup> (Olietåge)	TWA: 1 mg/m <sup>3</sup> (Oljetåke)	LLV: 1 mg/m <sup>3</sup> STV: 3 mg/m <sup>3</sup> (Oljedimma)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5mg/m <sup>3</sup> (Öljysumu)	TWA: 1 mg/m <sup>3</sup> (Olietåge)	TWA: 1 mg/m <sup>3</sup> (Oljetåke)	LLV: 1 mg/m <sup>3</sup> STV: 3 mg/m <sup>3</sup> (Oljedimma)

Chemical Name	Czech Republic	Hungary	Bulgaria	Romania
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> Ceiling: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> Ceiling: 10 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>

Chemical Name	Greece	Cyprus	Turkey	Malta
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup>			
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup>			

Chemical Name	Belgium	Luxembourg	Iceland	Croatia
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>			
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m <sup>3</sup> STEL: 10 mg/m <sup>3</sup>			

Chemical Name	Russia	Estonia	Latvia	Lithuania
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup> STEL: 3 mg/m <sup>3</sup>

Chemical Name	Belarus	Ukraine	Slovakia	Slovenia
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5mg/m <sup>3</sup>	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5mg/m <sup>3</sup>	

**Legend:**

(s) - Skin

TWA - Time-Weighted Average

STEL - Short Term Exposure Limit

Ceiling - Ceiling Value

**Derived No Effect Level (DNEL)****Workers Systemic toxicity****Workers Local effects**

Consumers Systemic toxicity

Consumers Local effects

Predicted No Effect Concentration (PNEC)

## 8.2. Exposure controls

<b>Engineering Measures</b>	Ensure adequate ventilation, especially in confined areas.
<b>Personal protective equipment</b>	
<b>Eye Protection</b>	Safety glasses with side-shields.
<b>Hand Protection</b>	Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.
<b>Skin and body protection</b>	Long sleeved clothing.
<b>Respiratory protection</b>	No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
<b>Hygiene measures</b>	Wear personal protective equipment. Avoid contact with skin, eyes and clothing. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.
<b>Environmental Exposure Controls</b>	No special environmental precautions required.
<b>Thermal hazards</b>	None under normal use conditions

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

<b>Physical state @20°C</b>	liquid	<b>Appearance</b>	clear amber
<b>Odor</b>	Hydrocarbon-like	<b>Odor Threshold</b>	Not Applicable
<u>Property</u>	<u>Values</u>		<u>Note</u>
<b>pH</b>	No information available		
<b>Melting Point / Freezing Point</b>	No information available		
<b>Boiling point/boiling range</b>	No information available		
<b>Flash point</b>	230 °C / 446 °F		ASTM D 92
<b>Evaporation rate</b>	No information available		
<b>Flammability (solid, gas)</b>	No information available		
<b>Flammability Limits in Air</b>			
<b>upper flammability limit</b>	No information available		
<b>Lower flammability limit</b>	No information available		
<b>Vapor pressure</b>	No information available		
<b>Vapor density</b>	No information available		
<b>Relative density</b>	0.862		@15°C
<b>Solubility(ies)</b>	Insoluble in water		
<b>Partition coefficient: n-octanol/water</b>	Not Applicable		
<b>Autoignition temperature</b>	No information available		
<b>Decomposition temperature</b>	No information available		
<b>Viscosity, kinematic</b>	87.65 cSt @ 40 °C		ASTM D 445
<b>Explosive properties</b>	Not Applicable		
<b>Oxidizing Properties</b>	Not Applicable		

**9.2. Other information**

Viscosity, kinematic (100°C)	14.21 cSt @ 100°C	ASTM D 445
Pour point	-36 °C / -33 °F	ASTM D 97
VOC Content (ASTM E-1868-10)	No information available	
VOC content	No information available	

**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

None under normal use conditions

**10.2. Chemical stability**

Stable under normal conditions

**10.3. Possibility of hazardous reactions**

None under normal use conditions

**10.4. Conditions to avoid**

Keep away from open flames, hot surfaces and sources of ignition, Extremes of temperature and direct sunlight

**10.5. Incompatible Materials**

Oxidizing agents

**10.6. Hazardous decomposition products**

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1. Information on toxicological effects****Product Information - Principle Routes of Exposure**

Inhalation	None known
Eye contact	None known
Skin contact	Repeated or prolonged skin contact may cause allergic reactions with susceptible persons
Ingestion	None known

**Acute toxicity - Product Information**

Product does not present an acute toxicity hazard based on known information.

**Acute toxicity - Component Information**

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	

<b>Skin corrosion/irritation</b>	Based on available data, the classification criteria are not met.
<b>Serious eye damage/eye irritation</b>	Based on available data, the classification criteria are not met.
<b>Sensitization</b>	
<b>Respiratory Sensitization</b>	Based on available data, the classification criteria are not met.
<b>Skin sensitization</b>	Repeated contact may cause allergic reactions in very susceptible persons.
<b>Germ Cell Mutagenicity</b>	Based on available data, the classification criteria are not met.
<b>Carcinogenicity</b>	Based on available data, the classification criteria are not met.
<b>Reproductive toxicity</b>	Based on available data, the classification criteria are not met.
<b>Specific target organ systemic toxicity (single exposure)</b>	Based on available data, the classification criteria are not met
<b>Specific target organ systemic toxicity (repeated exposure)</b>	Based on available data, the classification criteria are not met
<b>Aspiration hazard</b>	Based on available data, the classification criteria are not met.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

No special environmental measures are necessary

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to microorganisms	Toxicity to daphnia and other aquatic invertebrates
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts		1.0 - 5.0: 96 h Pimephales promelas mg/L LC50 static 10.0 - 35.0: 96 h Pimephales promelas mg/L LC50 semi-static		1 - 1.5: 48 h Daphnia magna mg/L EC50

### 12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

### 12.3. Bioaccumulative potential

No information available

### 12.4. Mobility in soil

The product is insoluble and floats on water

### 12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).



**12.6. Other adverse effects**

None known

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1. Waste treatment methods****Waste from Residues / Unused Products**

Dispose of in accordance with local regulations

**Contaminated packaging**

Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.

**Other Data**

According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

**SECTION 14: TRANSPORT INFORMATION****14.1. UN-Number**

Not regulated

**14.2. UN proper shipping name**

Not regulated

**14.3. Transport hazard class**

Not regulated

**14.4. Packing group**

Not regulated

**14.5. Environmental Hazards**

None

**14.6. Special precautions for users**

None

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable

**IMDG/IMO**

Not regulated

**ADR/RID**

Not regulated

**IATA**

Not regulated

**ADN**

Not regulated

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008)  
Registration, Evaluation, Authorization, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

#### WGK Classification

Hazard to water/Class 2

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), heavy hydrocracked	64741-76-0	265-077-7	01-2119486951-26-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx

Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	01-2119486452-34-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx

## 15.2. Chemical Safety Assessment

No information available

## SECTION 16: OTHER INFORMATION

### Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity  
 Asp. Tox. - Aspiration Toxicity  
 Acute Tox. - Acute Toxicity  
 Aquatic Acute - Acute Aquatic Toxicity  
 Aquatic Chronic - Chronic Aquatic Toxicity  
 Eye Dam. - Eye Damage  
 Eye Irrit. - Eye Irritation  
 Skin Corr. - Skin Corrosion  
 Skin Irrit. - Skin Irritation  
 Skin Sens. - Skin Sensitizer  
 Resp. Sens. - Respiratory Sensitizer  
 STOT SE - Specific target organ systemic toxicity (Single exposure)  
 STOT RE - Specific target organ systemic toxicity (repeated exposure)  
 VOC - Volatile organic compounds

**Full text of H-Statements referred to under sections 2 and 3**

<ul style="list-style-type: none"> <li>• H224 - Extremely flammable liquid and vapor</li> <li>• H225 - Highly flammable liquid and vapor</li> <li>• H226 - Flammable liquid and vapor</li> <li>• H270 - May cause or intensify fire; oxidizer</li> <li>• H271 - May cause fire or explosion; strong oxidizer</li> <li>• H272 - May intensify fire; oxidizer</li> <li>• H290 - May be corrosive to metals</li> <li>• H300 - Fatal if swallowed</li> <li>• H301 - Toxic if swallowed</li> <li>• H302 - Harmful if swallowed</li> <li>• H304 - May be fatal if swallowed and enters airways</li> <li>• H310 - Fatal in contact with skin</li> <li>• H311 - Toxic in contact with skin</li> <li>• H312 - Harmful in contact with skin</li> <li>• H314 - Causes severe skin burns and eye damage</li> <li>• H315 - Causes skin irritation</li> <li>• H317 - May cause an allergic skin reaction</li> <li>• H318 - Causes serious eye damage</li> <li>• H319 - Causes serious eye irritation</li> <li>• H330 - Fatal if inhaled</li> <li>• H331 - Toxic if inhaled</li> <li>• H332 - Harmful if inhaled</li> <li>• H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled</li> <li>• H335 - May cause respiratory irritation</li> <li>• H336 - May cause drowsiness or dizziness</li> <li>• H340 - May cause genetic defects</li> </ul>	<ul style="list-style-type: none"> <li>• H341 - Suspected of causing genetic defects</li> <li>• H350 - May cause cancer</li> <li>• H351 - Suspected of causing cancer</li> <li>• H360 - May damage fertility or the unborn child</li> <li>• H361 - Suspected of damaging fertility or the unborn child</li> <li>• H362 - May cause harm to breast-fed children</li> <li>• H370 - Causes damage to organs</li> <li>• H371 - May cause damage to organs</li> <li>• H372 - Causes damage to organs through prolonged or repeated exposure</li> <li>• H373 - May cause damage to organs through prolonged or repeated exposure</li> <li>• H400 - Very toxic to aquatic life</li> <li>• H410 - Very toxic to aquatic life with long lasting effects</li> <li>• H411 - Toxic to aquatic life with long lasting effects</li> <li>• H412 - Harmful to aquatic life with long lasting effects</li> <li>• H413 - May cause long lasting harmful effects to aquatic life</li> <li>• H360Df - May damage the unborn child. Suspected of damaging fertility</li> <li>• H360D - May damage the unborn child</li> <li>• H360FD - May damage fertility. May damage the unborn child</li> <li>• H360F - May damage fertility</li> <li>• H361d - Suspected of damaging the unborn child</li> <li>• H361fd - Suspected of damaging fertility. Suspected of damaging the unborn child</li> <li>• H361f - Suspected of damaging fertility</li> <li>• EUH066 - Repeated exposure may cause skin dryness or cracking</li> <li>• EUH210 - Safety data sheet available on request</li> <li>• EUH208 - May produce an allergic reaction</li> </ul>
---	--

**Exposure scenario**

No information available

**Revision Date:**

09-29-2016

**Revision Note****Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.