

SAFETY DATA SHEET

Issuing Date: 10-09-2014

Revision Date: 10-09-2014

Version 1

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name Product Code(s) Gulf Formula ULE, SAE 5W-30 01127/5W-30/2

1.2. <u>Relevant identified uses of the substance or mixture and uses advised against</u>

Recommended useEngine oilUses advised againstAny other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

Gulf Oil Supply Company Limited B2 Industry Street, Qormi, QRM 3000, Malta +44 207 321 6219 products@gulfoilltd.com sds@gulfoilltd.com

1.4. Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276 (+) 1 760 476 3961 Code 334276 (+) 32 (0) 3241 33 55

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

2.2 Label elements

Signal Word None

Hazard Statements

EUH210 - Safety data sheet available on request

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	25% - 50%	Asp. Tox. 1 (H304) (EUH066)	-
Bis(nonylphenyl)amine	253-249-4	36878-20-3	1% - 2.5%	Aquatic Chronic 4 (H413)	01-2119488911-28-xx xx

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

See Section 15 for additional information on base oils.

** Substances for which there are Community workplace exposure limits

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice	If symptoms persist, call a physician.			
Inhalation	Move to fresh air.			
Skin contact	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use.			
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while rinsing.			
Ingestion	Clean mouth with water and afterwards drink plenty of water. Do not induce vomiting without medical advice.			
Protection of First-aiders	Use personal protective equipment.			
4.2. Most important symptoms and effects, both acute and delayed				
Main Symptoms	None			
4.3. Indication of immediate medical attention and special treatment needed				

Notes to physician

Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use water spray, fog, Carbon dioxide, foam or dry chemical, Cool containers / tanks with water spray.

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

Water runoff can cause environmental damage. Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). In the event of fire and/or explosion do not breathe fumes. This material creates a fire hazard because it floats on water. Combustible material.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Advice for non-emergency Material can create slippery conditions. personnel

Advice for emergency responders For personal protection see section 8.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Keep away from open flames, hot surfaces and sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition.

Incompatible Materials

Oxidizing agents

7.3. Specific end uses

Recommended use

Engine oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	The United Kingdom	France	Spain
Highly refined base oil (Viscosity >20.5 cSt @40°C)				VLA-EC: 10 mg/m ³ VLA-ED: 5 mg/m ³
Highly refined, low viscosity				VLA-EC: 10 mg/m ³
mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt				VLA-ED: 5 mg/m ³
@40°C)				

Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined base oil (Viscosity >20.5 cSt @40°C)				STEL: 10 mg/m ³ TWA: 5 mg/m ³ (Mist)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)				STEL: 10 mg/m ³ TWA: 5 mg/m ³ (Mist)

Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m ³ STV: 3 mg/m ³ (Oljedimma)
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m ³ (Olietåge)	TWA: 1 mg/m ³ (Oljetåke)	LLV: 1 mg/m³ STV: 3 mg/m³ (Oljedimma)

Derived No Effect Level (DNEL)

Workers Systemic toxicity

Chemical Name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation
			exposure			exposure
Bis(nonylphenyl)amine		0,62 mg/kg	4,37 mg/m ³			

Workers Local effects

Consumers Systemic toxicity

	Chemical Name	Long term - Oral exposure	Long term - Dermal exposure	Long term - Inhalation exposure	Short term - Oral Exposure	Short term - Dermal exposure	Short term - Inhalation exposure
Γ	Bis(nonylphenyl)amine	0,31 mg/kg	0,31 mg/kg	1,09 mg/m ³			

Consumers Local effects

Predicted No Effect Concentration (PNEC)

Chemical Name	Fresh water	Sea water	Fresh water sediment	Sea sediment	Soil
Bis(nonylphenyl)amine	0.1 mg/L	0.01 mg/L	132000 mg/kg	13200 mg/kg	263000 mg/kg

8.2. Exposure controls

Engineering Measures	Ensure adequate ventilation, especially in confined areas.
Personal protective equipment Eye Protection Hand Protection	Safety glasses with side-shields. Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. Barrier creams may help to protect the exposed areas of skin, they should however not be applied once exposure has occurred.
Skin and body protection Respiratory protection	Long sleeved clothing. Apron. Impervious gloves. No special protective equipment required. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
Hygiene measures	Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.
Environmental Exposure Controls Thermal hazards	No special environmental precautions required. None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°C	liquid	Appearance	clear amber
Odor	Hydrocarbon-like	Odor Threshold	Not Applicable
<u>Property</u> pH Melting/freezing point Boiling point/boiling range Flash Point	<u>Values</u> No information available. No information available No information available 230 °C / 446 °F		Note

Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limits in Air		
upper flammability limit	No information available	
lower flammability limit	No information available	
Vapor pressure	No information available	
Vapor density	No information available	
Relative density	0.8556	@15°C
Solubility(ies)	Insoluble in water	
Partition coefficient: n-octanol/w	aterNot Applicable	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Viscosity, kinematic	70.8 cSt @ 40 °C	ASTM D 445
Explosive properties	Not Applicable	
Oxidizing Properties	Not Applicable	
9.2 Other information		
Viscosity, kinematic (100°C) Pour point	12.2 cSt @ 100°C -39 °C / -38 °F	ASTM D 445 ASTM D 97

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of ignition

10.5. Incompatible Materials

Oxidizing agents

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation None known

Eye contact None known

01127/5W-30/2 - Gulf Formula ULE, SAE 5W-30

Skin contact None known

Ingestion None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information.

Acute toxicity - Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Bis(nonylphenyl)amine	> 5000 mg/kg(Rat)	> 2000 mg/kg (Rat)	

Skin corrosion/irritation	None known.
Serious eye damage/eye irritation	None known.
Sensitization Respiratory Sensitization Skin sensitization	None known. None known.
Germ Cell Mutagenicity	None known.
Carcinogenicity	None known.
Repeated Dose Toxicity	None known.
Reproductive toxicity	None known.
Specific target organ systemic toxicity (single exposure)	None known
Specific target organ systemic toxicity (repeated exposure)	None known
Aspiration hazard	None known.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecotoxicity effects

Chemical Name	Toxicity to algae	Toxicity to fish	Toxicity to	Toxicity to daphnia and
			microorganisms	other aquatic invertebrates

No special environmental measures are necessary

01127/5W-30/2 - Gulf Formula ULE, SAE 5W-30

Bis(nonylphenyl)amine	>100: 72 h Desmodesmus	>100: 96 h Danio rerio mg/L	>100: 48 h Daphnia magna
	subspicatus mg/L EC50	LC50	mg/L EC50
		1000: 96 h Pimephales	14 - 28: 96 h Mysidopsis
		promelas mg/L LC50	bahia mg/L LC50
		semi-static	_

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused Products	Dispose of in accordance with local regulations
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal. Observe all label precautions until container is cleaned, reconditioned or destroyed.
Other information	According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMO	Not regulated

ADR/RID Not regulated

ICAO/IATA Not regulated

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008) Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx

01127/5W-30/2 - Gulf Formula ULE, SAE 5W-30

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	01-2119486452-34-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet Repr.-Reproduction toxicity Asp. Tox. - Aspiration Toxicity Acute Tox. - Acute Toxicity Aquatic Acute - Acute Aquatic Toxicity Aquatic Chronic - Chronic Aquatic Toxicity Eye Dam. - Eye Damage Eye Irrit. - Eye Irritation Skin Corr. - Skin Corrosion Skin Irrit. - Skin Irritation Skin Sens. - Skin Sensitizer Resp. Sens. - Respiratory Sensitizer STOT SE - Specific target organ systemic toxicity (Single exposure) STOT RE - Specific target organ systemic toxicity (repeated exposure) VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor	+ H241 Supported of equaina appatic defects
H225 - Highly flammable liquid and vapor	 H341 - Suspected of causing genetic defects H350 - May cause cancer
H226 - Flammable liquid and vapor	H351 - Suspected of causing cancer
• H270 - May cause or intensify fire; oxidizer	H360 - May damage fertility or the unborn child
H271 - May cause fire or explosion; strong oxidizer	H361 - Suspected of damaging fertility or the unborn child
H272 - May intensify fire; oxidizer	H362 - May cause harm to breast-fed children
 H290 - May be corrosive to metals 	H370 - Causes damage to organs
 H300 - Fatal if swallowed 	 H371 - May cause damage to organs
H301 - Toxic if swallowed	H372 - Causes damage to organs through prolonged or repeated
 H302 - Harmful if swallowed 	exposure
 H304 - May be fatal if swallowed and enters airways 	 H373 - May cause damage to organs through prolonged or repeated
 H310 - Fatal in contact with skin 	exposure
H311 - Toxic in contact with skin	H400 - Very toxic to aquatic life
 H312 - Harmful in contact with skin 	 H410 - Very toxic to aquatic life with long lasting effects
 H314 - Causes severe skin burns and eye damage 	 H411 - Toxic to aquatic life with long lasting effects
H315 - Causes skin irritation	 H412 - Harmful to aquatic life with long lasting effects
 H317 - May cause an allergic skin reaction 	 H413 - May cause long lasting harmful effects to aquatic life
H318 - Causes serious eye damage	H360Df - May damage the unborn child. Suspected of damaging fertility
H319 - Causes serious eye irritation	H360D - May damage the unborn child
• H330 - Fatal if inhaled	H360FD - May damage fertility. May damage the unborn child
• H331 - Toxic if inhaled	• H360F - May damage fertility
H332 - Harmful if inhaled	 H361d - Suspected of damaging the unborn child
• H334 - May cause allergy or asthma symptoms or breathing difficulties	• H361fd - Suspected of damaging fertility. Suspected of damaging the
if inhaled	unborn child
H335 - May cause respiratory irritation	H361f - Suspected of damaging fertility
H336 - May cause drowsiness or dizziness	• EUH066 - Repeated exposure may cause skin dryness or cracking
• H340 - May cause genetic defects	• EUH210 - Safety data sheet available on request
	• EUH208 - May produce an allergic reaction

Exposure scenario

No information available

Issuing Date:	10-09-2014
Revision Date:	10-09-2014
Revision Note	Not Applicable.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.