

SAFETY DATA SHEET

Gulf Pride 2T Plus

05111/1

Issuing Date: 08-16-2016 Revision Date: 08-16-2016 Version 2

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product Name Gulf Pride 2T Plus

Product Code(s): 05111/1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use 2-Stroke Engine Oil

Uses advised against Any other purpose.

1.3. Details of the supplier of the safety data sheet

Supplier

Gulf Oil Supply Company Limited B2 Industry Street, Qormi, QRM 3000, Malta +44 207 321 6219 products@gulfoilltd.com sds@gulfoilltd.com

1.4. Emergency telephone number

Europe (+) 44 808 189 0979 Code 334276 (+) 1 760 476 3961 Code 334276 (+) 32 (0) 3241 33 55

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [GHS]

2.2. Label Elements

Signal Word

None

Hazard Statements

EUH210 - Safety data sheet available on request

2.3. Other hazards

No information available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances / 3.2. Mixtures

This product is a mixture. Health hazard information is based on its ingredients

Chemical Name	EC-No	CAS-No	Weight %	Classification (Reg. 1272/2008)	REACH Registration Number
Highly refined base oil (Viscosity >20.5 cSt @40°C)	-	-	50% - 100%	**	-
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	-	-	10% - 25%	Asp. Tox. 1 (H304) (EUH066)	-
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	-	-	1% - 2.5%	Asp. Tox. 1 (H304) (EUH066)	-

Additional information

Product containing mineral oil with less than 3% DMSO extract as measured by IP 346 See Section 15 for additional information on base oils.

Full text of H- and EUH-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of first-aid measures

General advice If symptoms persist, call a physician.

Inhalation Move to fresh air.

Wash off immediately with soap and plenty of water. Remove and wash contaminated Skin contact

clothing before re-use.

Rinse thoroughly with plenty of water, also under the eyelids. Keep eye wide open while Eye contact

rinsing.

Clean mouth with water. Drink plenty of water. Do not induce vomiting without medical Ingestion

advice.

Protection of First-aiders Use personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

None **Main Symptoms**

4.3. Indication of immediate medical attention and special treatment needed

Notes to physician Treat symptomatically.

SECTION 5: FIRE FIGHTING MEASURES

^{**} Substances for which there are Community workplace exposure limits

5.1. Extinguishing media

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment:, Use CO2, dry chemical, or foam, Water spray or fog, Cool containers / tanks with water spray

Extinguishing media which shall not be used for safety reasons

Do not use a solid water stream as it may scatter and spread fire

5.2. Special hazards arising from the substance or mixture

Special Hazard

Combustible material. Risk of ignition. In the event of fire and/or explosion do not breathe fumes. Thermal decomposition can lead to release of irritating gases and vapors. Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). This material creates a fire hazard because it floats on water.

Hazardous Decomposition Products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide

5.3. Advice for firefighters

Special protective equipment for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition. Ensure adequate ventilation.

Advice for non-emergency

Eliminate all ignition sources if safe to do so.

personnel

For personal protection see section 8. Advice for emergency responders

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system.

6.3. Methods and materials for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Dike to collect large liquid spills.

6.4. Reference to other sections

See Section 8/12/13 for additional information

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for safe handling

Ensure adequate ventilation. Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice. Remove all sources of ignition.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures/Storage conditions

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from open flames, hot surfaces and sources of ignition. Keep out of the reach of children.

Incompatible Materials

Oxidizing agents

7.3. Specific end uses

Recommended use

2-Stroke Engine Oil

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Chemical Name	European Union	United Kingdom	France	Spain
Highly refined base oil				VLA-EC: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)				VLA-ED: 5 mg/m ³
Highly refined, low viscosity				VLA-EC: 10 mg/m ³
base oil (Viscosity <7 cSt				VLA-ED: 5 mg/m ³
@40°C)				_
Highly refined, low viscosity				VLA-EC: 10 mg/m ³
mineral oils/hydrocarbons				VLA-ED: 5 mg/m ³
(Viscosity >7 - <20.5 cSt				
@40°C)				

Chemical Name	Germany	Italy	Portugal	The Netherlands
Highly refined base oil		TWA: 5 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m³	
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)		TWA: 5 mg/m³	TWA: 5 mg/m³ STEL: 10 mg/m³	TWA: 5 mg/m³
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)		TWA: 5 mg/m³	TWA: 5 mg/m³ STEL: 10 mg/m³	TWA: 5 mg/m³

Chemical Name	Austria	Switzerland	Poland	Ireland
Highly refined base oil			TWA: 5 mg/m ³	STEL: 10 mg/m ³
(Viscosity >20.5 cSt @40°C)			STEL: 10 mg/m³	TWA: 5 mg/m ³
				(Mist)
Highly refined, low viscosity			TWA: 5 mg/m ³	STEL: 10 mg/m ³
base oil (Viscosity <7 cSt			STEL: 10 mg/m³	TWA: 5 mg/m ³
@40°C)				(Mist)
Highly refined, low viscosity			TWA: 5 mg/m ³	STEL: 10 mg/m ³
mineral oils/hydrocarbons			STEL: 10 mg/m³	TWA: 5 mg/m ³
(Viscosity >7 - <20.5 cSt				(Mist)
@40°C)				

Chemical Name	Finland	Denmark	Norway	Sweden
Highly refined base oil (Viscosity	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	LLV: 1 mg/m ³

>20.5 cSt @40°C)				STV: 3 mg/m ³
_ ,				(Oljedimma)
Highly refined, low viscosity base oil	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	LLV: 1 mg/m ³
(Viscosity <7 cSt @40°C)				STV: 3 mg/m ³
				(Oljedimma)
Highly refined, low viscosity mineral	TWA: 5mg/m³ (Öljysumu)	TWA: 1 mg/m³ (Olietåge)	TWA: 1 mg/m³ (Oljetåke)	LLV: 1 mg/m ³
oils/hydrocarbons (Viscosity >7 -				STV: 3 mg/m ³
<20.5 cSt @40°C)				(Oliedimma)

Chemical Name	Czech Republic	Hungary	Bulgaria	Romania
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m³ Ceiling: 10 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³ STEL: 10 mg/m³
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	TWA: 5 mg/m³ Ceiling: 10 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³ STEL: 10 mg/m³
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m³ Ceiling: 10 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³	TWA: 5 mg/m³ STEL: 10 mg/m³

Chemical Name	Greece	Cyprus	Turkey	Malta
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m³			
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	TWA: 5 mg/m³			
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m³			

Chemical Name	Belgium	Luxembourg	Iceland	Croatia
Highly refined base oil (Viscosity >20.5 cSt @40°C)	TWA: 5 mg/m ³ STEL: 10 mg/m ³			
Highly refined, low viscosity base oil (Viscosity <7 cSt				
@40°C) Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	TWA: 5 mg/m³ STEL: 10 mg/m³			

Chemical Name	Russia	Estonia	Latvia	Lithuania
Highly refined base oil			TWA: 5 mg/m ³	TWA: 1 mg/m ³
(Viscosity >20.5 cSt @40°C)				STEL: 3 mg/m ³
Highly refined, low viscosity			TWA: 5 mg/m ³	TWA: 1 mg/m ³
base oil (Viscosity <7 cSt				STEL: 3 mg/m ³
@40°C)				
Highly refined, low viscosity			TWA: 5 mg/m ³	TWA: 1 mg/m ³
mineral oils/hydrocarbons				STEL: 3 mg/m ³
(Viscosity >7 - <20.5 cSt				
@40°C)				

Chemical Name	Belarus	Ukraine	Slovakia	Slovenia
Highly refined base oil (Viscosity >20.5 cSt @40°C)			TWA: 5mg/m ³	
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)			TWA: 5mg/m ³	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)			TWA: 5mg/m³	

Derived No Effect Level (DNEL)

Workers Systemic toxicity

Workers Local effects

Consumers Systemic toxicity

Consumers Local effects

Predicted No Effect Concentration (PNEC)

8.2. Exposure controls

Engineering Measures Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eve Protection Hand Protection Safety glasses with side-shields.

Protective gloves. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the

specific local conditions under which the product is used, such as the danger of cuts. abrasion. Barrier creams may help to protect the exposed areas of skin, they should

however not be applied once exposure has occurred.

Skin and body protection Respiratory protection

Long sleeved clothing.

No special protective equipment required. In case of mist, spray or aerosol exposure wear

ASTM D 92

suitable personal respiratory protection and protective suit.

Do not eat, drink or smoke when using this product. Handle in accordance with good Hygiene measures

industrial hygiene and safety practice.

Environmental Exposure Controls

No special environmental precautions required.

Thermal hazards

None under normal use conditions

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state @20°C liquid Appearance clear amber Hydrocarbon-like Odor **Odor Threshold** Not Applicable

Property Values Note

No information available

No information available

pН **Melting Point / Freezing Point**

Boiling point/boiling range

No information available 86 °C / 187 °F Flash point

No information available **Evaporation rate**

Flammability (solid, gas) No information available

Flammability Limits in Air

upper flammability limit No information available Lower flammability limit No information available

No information available Vapor pressure Vapor density No information available

Revision Date: 08-16-2016

@15°C Relative density 0.8704

Solubility(ies) Insoluble in water Partition coefficient: n-octanol/water Not Applicable

Autoignition temperature No information available **Decomposition temperature** No information available

Viscosity, kinematic 46.22 cSt @ 40 °C ASTM D 445

Not Applicable **Explosive properties Oxidizing Properties** Not Applicable

9.2. Other information

Viscosity, kinematic (100°C) 7.76 cSt @ 100°C ASTM D 445 -15 °C / 5 °F Pour point ASTM D 97

VOC Content (ASTM E-1868-10) No information available **VOC** content No information available

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

None under normal use conditions

10.2. Chemical stability

Stable under normal conditions

10.3. Possibility of hazardous reactions

None under normal use conditions

10.4. Conditions to avoid

Heat, flames and sparks, Keep away from open flames, hot surfaces and sources of ignition, Heat (temperatures above flash point), sparks, ignition points, flames, static electricity

10.5. Incompatible Materials

Oxidizing agents

10.6. Hazardous decomposition products

Incomplete combustion and thermolysis produces potentially toxic gases such as carbon monoxide and carbon dioxide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Product Information - Principle Routes of Exposure

Inhalation None known

Eye contact None known

None known Skin contact

Ingestion None known

Acute toxicity - Product Information

Product does not present an acute toxicity hazard based on known information.

Acute toxicity - Component Information

Chemical Name	LD50 Oral (Rat)	LD50 Dermal (Rat/Rabbit)	LC50 Inhalation
Highly refined base oil (Viscosity >20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined, low viscosity base oil (Viscosity <7 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	
Highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C)	>2000 mg/kg	>2000 mg/kg	

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Serious eye damage/eye irritation

Sensitization

Respiratory Sensitization Based on available data, the classification criteria are not met. Skin sensitization

Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ systemic toxicity (single exposure)

Based on available data, the classification criteria are not met

Specific target organ systemic toxicity (repeated exposure)

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met. **Aspiration hazard**

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

No special environmental measures are necessary

12.2. Persistence and degradability

The product is not readily biodegradable, but it can be degraded by micro-organisms, it is regarded as being inherently biodegradable.

12.3. Bioaccumulative potential

No information available

12.4. Mobility in soil

The product is insoluble and floats on water

Revision Date: 08-16-2016

12.5. Results of PBT and vPvB assessment

This preparation contains no substance considered to be persistent, bioaccumulating nor toxic (PBT). This preparation contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

12.6. Other adverse effects

None known

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste from Residues / Unused

Products

Dispose of in accordance with local regulations

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal. Observe all label precautions until container is cleaned, reconditioned or

destroyed.

Other Data According to the European Waste Catalogue, Waste Codes are not product specific, but

application specific. Waste codes should be assigned by the user based on the application

for which the product was used.

SECTION 14: TRANSPORT INFORMATION

14.1. UN-Number

Not regulated

14.2. UN proper shipping name

Not regulated

14.3. Transport hazard class

Not regulated

14.4. Packing group

Not regulated

14.5. Environmental Hazards

None

14.6. Special precautions for users

None

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

IMDG/IMO Not regulated

Not regulated ADR/RID

<u>IATA</u> Not regulated

Not regulated ADN

SECTION 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

The Classification, Labeling and Packaging of Substances and Mixtures (CLP) Regulation (EC 1272/2008) Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

WGK Classification Low hazard to water/Class 1

The highly refined base oil (Viscosity >20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487081-40-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed heavy	64742-70-7	265-174-4	01-2119487080-42-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	276-735-8	
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	276-736-3	01-2119555262-43-xxxx
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	72623-86-0	276-737-9	01-2119474878-16-xxxx
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	72623-87-1	276-738-4	01-2119474889-13-xxxx
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx
White mineral oil (petroleum)	8042-47-5	232-455-8	

The highly refined, low viscosity mineral oils/hydrocarbons (Viscosity >7 - <20.5 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8	01-2119488706-23-xxxx
Distillates (petroleum), solvent-refined light paraffinic	64741-89-5	265-091-3	01-2119487067-30-xxxx
Residual oils (petroleum), solvent deasphalted	64741-95-3	265-096-0	01-2119487081-40-xxxx
Distillates (petroleum), solvent-refined heavy naphthenic	64741-96-4	265-097-6	01-2119483621-38-xxxx
Distillates (petroleum), solvent-refined light naphthenic	64741-97-5	265-098-1	01-2119480374-36-xxxx
Residual oils (petroleum), solvent-refined	64742-01-4	265-101-6	01-2119488707-21-xxxx

Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	01-2119467170-45-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Residual oils (petroleum), hydrotreated	64742-57-0	265-160-8	01-2119489287-22-xxxx
Lubricating oils (petroleum), hydrotreated spent	64742-58-1	265-161-3	
Residual oils (petroleum), solvent-dewaxed	64742-62-7	265-166-0	01-2119480472-38-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Paraffin oils (petroleum), catalytic dewaxed light	64742-71-8	265-176-5	01-2119485040-48-xxxx
Dec-1-ene, homopolymer, hydrogenated	68037-01-4	500-183-1	01-2119486452-34-xxxx
Lubricating oils (petroleum), C>25, hydrotreated bright	72623-83-7	276-735-8	
stock-based			
Lubricating oils (petroleum), C20-50, hydrotreated neutral	72623-85-9	276-736-3	01-2119555262-43-xxxx
oil-based, high-viscosity			
Lubricating oils (petroleum), C15-30, hydrotreated neutral	72623-86-0	276-737-9	01-2119474878-16-xxxx
oil-based			
Lubricating oils (petroleum), C20-50, hydrotreated neutral	72623-87-1	276-738-4	01-2119474889-13-xxxx
oil-based			
Lubricating oils	74869-22-0	278-012-2	01-2119495601-36-xxxx

The highly refined, low viscosity base oil (Viscosity <7 cSt @40°C) contains one or more substance with the following CAS/EC numbers/REACH registration numbers:

Chemical Name	CAS-No	EC-No	REACH Registration Number
Distillates (petroleum), hydrotreated heavy paraffinic	63742-54-7	265-157-1	01-2119484627-25-xxxx
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	265-156-6	01-2119480375-34-xxxx
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	265-158-7	01-2119487077-29-xxxx
Distillates (petroleum), solvent-dewaxed light paraffinic	64742-56-9	265-159-2	01-2119480132-48-xxxx
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	265-169-7	01-2119471299-27-xxxx
Dec-1-ene, dimers, hydrogenated	68649-11-6	500-228-5	
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NOT AVAILABLE	926-141-6	01-2119456620-43-xxxx

15.2. Chemical Safety Assessment

No information available

SECTION 16: OTHER INFORMATION

Key or legend to abbreviations and acronyms used in the safety data sheet

Repr.-Reproduction toxicity

Asp. Tox. - Aspiration Toxicity

Acute Tox. - Acute Toxicity

Aquatic Acute - Acute Aquatic Toxicity

Aquatic Chronic - Chronic Aquatic Toxicity

Eye Dam. - Eye Damage

Eye Irrit. - Eye Irritation

Skin Corr. - Skin Corrosion

Skin Irrit. - Skin Irritation

Skin Sens. - Skin Sensitizer

Resp. Sens. - Respiratory Sensitizer

STOT SE - Specific target organ systemic toxicity (Single exposure)

STOT RE - Specific target organ systemic toxicity (repeated exposure)

VOC - Volatile organic compounds

Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor	H341 - Suspected of causing genetic defects
H225 - Highly flammable liquid and vapor	H350 - May cause cancer
H226 - Flammable liquid and vapor	H351 - Suspected of causing cancer
H270 - May cause or intensify fire; oxidizer	H360 - May damage fertility or the unborn child
 H271 - May cause fire or explosion; strong oxidizer 	H361 - Suspected of damaging fertility or the unborn child
H272 - May intensify fire; oxidizer	H362 - May cause harm to breast-fed children
H290 - May be corrosive to metals	H370 - Causes damage to organs
H300 - Fatal if swallowed	H371 - May cause damage to organs
H301 - Toxic if swallowed	H372 - Causes damage to organs through prolonged or repeated
H302 - Harmful if swallowed	exposure
 H304 - May be fatal if swallowed and enters airways 	H373 - May cause damage to organs through prolonged or repeated
H310 - Fatal in contact with skin	exposure
H311 - Toxic in contact with skin	H400 - Very toxic to aquatic life
H312 - Harmful in contact with skin	H410 - Very toxic to aquatic life with long lasting effects
 H314 - Causes severe skin burns and eye damage 	H411 - Toxic to aquatic life with long lasting effects
H315 - Causes skin irritation	H412 - Harmful to aquatic life with long lasting effects
H317 - May cause an allergic skin reaction	 H413 - May cause long lasting harmful effects to aquatic life
H318 - Causes serious eye damage	• H360Df - May damage the unborn child. Suspected of damaging fertility
H319 - Causes serious eye irritation	H360D - May damage the unborn child
H330 - Fatal if inhaled	H360FD - May damage fertility. May damage the unborn child
H331 - Toxic if inhaled	H360F - May damage fertility
H332 - Harmful if inhaled	H361d - Suspected of damaging the unborn child
 H334 - May cause allergy or asthma symptoms or breathing difficulties 	 H361fd - Suspected of damaging fertility. Suspected of damaging the
if inhaled	unborn child
H335 - May cause respiratory irritation	H361f - Suspected of damaging fertility
H336 - May cause drowsiness or dizziness	• EUH066 - Repeated exposure may cause skin dryness or cracking
H340 - May cause genetic defects	EUH210 - Safety data sheet available on request
	EUH208 - May produce an allergic reaction

Exposure scenario

No information available

Revision Date: 08-16-2016

Revision Note

(M)SDS sections updated, 15.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.