



Prestone



SAFETY DATA SHEET Holts Radweld

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Holts Radweld
Product number	HREP0021A, HREP0021B, HREP0032A, 52032020001, HREP0001B, HREP0002A, HREP0002B, HREP0801A, HREP0901A, RW2GR, RW2HPR, RW2R, RW2RU, RW2SKR, 52032020002, RW4BUL, RW4R, RW4SFR, RW4SKR, RW9, 52032020022, 52032020089, 52032020100, 52032030002, 52032030011, 52032030022, HREP0001A, HREP0061A
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product.
------------------------	--------------------------

1.3. Details of the supplier of the safety data sheet

Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs Out of office hours Tel: 020 7358 9167
----------------------------	---

National emergency telephone number <https://poisoncentres.echa.europa.eu/>

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Not Classified
Health hazards	Not Classified
Environmental hazards	Not Classified

2.2. Label elements

Hazard statements	NC Not Classified
Precautionary statements	P102 Keep out of reach of children. P101 If medical advice is needed, have product container or label at hand. P501 Dispose of contents/ container in accordance with local regulations.

Holts Radweld

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHANOL	1-5%
CAS number: 64-17-5	EC number: 200-578-6
Classification	Classification (67/548/EEC or 1999/45/EC)
Flam. Liq. 2 - H225	F;R11

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Treat symptomatically.
Inhalation	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Ingestion	Never give anything by mouth to an unconscious person. Do not induce vomiting. Rinse mouth thoroughly with water. Give plenty of water to drink. Get medical attention if any discomfort continues.
Skin contact	Remove affected person from source of contamination. Get medical attention if irritation persists after washing.
Eye contact	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	This is unlikely to occur but symptoms similar to those of ingestion may develop.
Ingestion	May cause discomfort if swallowed.
Skin contact	Skin irritation. Prolonged skin contact may cause redness and irritation.
Eye contact	Irritation of eyes and mucous membranes. Prolonged contact may cause redness and/or tearing.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically.
-----------------------------	------------------------

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media The product is not flammable. Use fire-extinguishing media suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	In case of fire, toxic and corrosive gases may be formed. No unusual fire or explosion hazards noted.
Hazardous combustion products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Holts Radweld

Protective actions during firefighting No specific firefighting precautions known.

Special protective equipment for firefighters Use protective equipment appropriate for surrounding materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet.

6.2. Environmental precautions

Environmental precautions Do not discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush contaminated area with plenty of water. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container.

Storage class Unspecified storage.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

Short-term exposure limit (15-minute): WEL

2-Methoxymethylethoxypropanol

Long-term exposure limit (8-hour TWA): WEL 50 ppm 308 mg/m³

Sk

SODIUM HYDROXIDE

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 2 mg/m³

PHOSPHORIC ACID ...%

Long-term exposure limit (8-hour TWA): WEL 1 mg/m³

Short-term exposure limit (15-minute): WEL 2 mg/m³

METHANOL

Holts Radweld

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³

Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

Sk

WEL = Workplace Exposure Limit

Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

NON HAZARDOUS INGREDIENTS

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. It is recommended that gloves are made of the following material: Rubber (natural, latex). EN374

Other skin and body protection

Wear appropriate clothing to prevent any possibility of skin contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke.

Respiratory protection

Respiratory protection not required.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance	Coloured liquid.
Colour	Brown.
pH	pH (concentrated solution): 10.0
Flash point	> 60°C Closed cup.
Relative density	1.022 @ 20°C
Solubility(ies)	Miscible with water.

9.2. Other information

Volatile organic compound This product contains a maximum VOC content of 5 %.

SECTION 10: Stability and reactivity

10.1. Reactivity

Holts Radweld

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions Not applicable. Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid excessive heat for prolonged periods of time.

10.5. Incompatible materials

Materials to avoid No specific material or group of materials is likely to react with the product to produce a hazardous situation.

10.6. Hazardous decomposition products

Hazardous decomposition products Fire creates: Carbon monoxide (CO). Carbon dioxide (CO₂).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

ATE oral (mg/kg) 89,272.96

Acute toxicity - dermal

ATE dermal (mg/kg) 267,818.88

Acute toxicity - inhalation

ATE inhalation (gases ppm) 624,910.73

ATE inhalation (vapours mg/l) 2,678.19

ATE inhalation (dusts/mists mg/l) 446.36

Inhalation No specific health hazards known.

Ingestion May cause discomfort if swallowed. May cause stomach pain or vomiting.

Skin contact Prolonged and frequent contact may cause redness and irritation.

Eye contact May cause eye irritation.

Acute and chronic health hazards This product has low toxicity. Only large quantities are likely to have adverse effects on human health.

SECTION 12: Ecological Information

Ecotoxicity Not regarded as dangerous for the environment. The product components are not classified as environmentally hazardous. However, large or frequent spills may have hazardous effects on the environment.

12.1. Toxicity

12.2. Persistence and degradability

Holts Radweld

Persistence and degradability The product is biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product is not bioaccumulating.

12.4. Mobility in soil

Mobility The product contains substances which are water-soluble and may spread in water systems.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009 No. 716).

Holts Radweld

EU legislation

Dangerous Substances Directive 67/548/EEC.
 Dangerous Preparations Directive 1999/45/EC.
 Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
 Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Authorisations (Title VII Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date	26/04/2017
Revision	1
SDS number	14894
Risk phrases in full	<p>Not classified.</p> <p>R10 Flammable.</p> <p>R11 Highly flammable.</p> <p>R22 Harmful if swallowed.</p> <p>R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.</p> <p>R34 Causes burns.</p> <p>R35 Causes severe burns.</p> <p>R37 Irritating to respiratory system.</p> <p>R38 Irritating to skin.</p> <p>R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.</p> <p>R41 Risk of serious damage to eyes.</p> <p>R48/22 Harmful: danger of serious damage to health by prolonged exposure if swallowed.</p> <p>R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>R66 Repeated exposure may cause skin dryness or cracking.</p> <p>R67 Vapours may cause drowsiness and dizziness.</p>
Hazard statements in full	H225 Highly flammable liquid and vapour.