

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 1 of 14

Epoxy Putty Stick - Under Water Cure - Part A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product Name: Epoxy Putty Stick - Under Water Cure - Part A

Product code: 8277, 8277H (A)



1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses: Not determined or not applicable.

Uses advised against: Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

1.3 Details of the manufacturer/supplier of the safety data sheet

Manufacturer:

United States

J-B Weld Company, LLC

1130 COMO ST.

SULPHUR SPRINGS, TX 75482

903-885-7696

info@jbweld.com

1.4 Emergency telephone number:

United States

CHEMTREC

Transportation Emergencies (24 hour): 800-424-9300 or

703-527-3887

Poison Control Centers (24 hour): medical emergencies 800-222-1222

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture:

Classification according to Regulation (EC) No. 1272/2008 (CLP):

Eye irritation, category 2A

Skin irritation, category 2

Skin sensitization, category 1

Chronic aquatic hazard, category 2

Hazard-determining components of labeling:

Epoxy resin

Diluent

Powder

2.2 Label elements

Hazard pictograms:



Signal word: Warning

Hazard statements:

H319 Causes serious eye irritation.

H315+H320 Causes skin and eye irritation.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P264 Wash skin and eyes thoroughly after handling.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 2 of 14

Epoxy Putty Stick - Under Water Cure - Part A

- P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337+P313 If eye irritation persists get medical advice/attention
P321 Specific treatment (see supplemental first aid instructions on this label).
P362 Take off contaminated clothing and wash before reuse
P302+P352 IF ON SKIN: Wash with plenty of soap and water.
P332+P313 If skin irritation occurs: Get medical advice/attention
P362+P364 Take off contaminated clothing and wash it before reuse.
P363 Wash contaminated clothing before reuse
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention
P391 Collect spillage
P501 Dispose of contents/container in accordance with local regulations.

2.3 Other hazards: None known

SECTION 3: Composition/information on ingredients

3.1 Substance: Not applicable.

3.2 Mixture:

Identification	Name	Classification according to Regulation (EC) No. 1272/2008 (CLP)	Weight %
CAS number: 14807-96-6 EC number: 238-877-9	Talc Powder	Not classified	<15
CAS number: 13463-67-7 EC number: 236-675-5	Titanium Dioxide	Not classified	<10
CAS number: 67762-90-7	Powder additive	Not classified	<1
CAS number: 65997-17-3 EC number: 266-046-0	Powder	Carc. 1B; H350	<25
CAS number: 37244-96-5	Powder	Not classified	<40
CAS number: 3101-60-8 EC number: 221-453-2	Diluent	Skin Sens. 1; H317 Skin Irrit. 2 ; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	<1
CAS number: 25068-38-6 EC number: 500-033-5	Epoxy resin	Skin Sens. 1; H317 Skin Irrit. 2 ; H315 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	<30

Additional information: None

Full Text of H and EUH statements: See section 16

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 3 of 14

Epoxy Putty Stick - Under Water Cure - Part A

SECTION 4: First aid measures

4.1 Description of first aid measures

General notes:

Not determined or not available.

Following inhalation:

Loosen clothing as necessary and position individual in a comfortable position

Maintain an unobstructed airway

Get medical advice/attention if you feel unwell

Following skin contact:

Rinse affected area with soap and water

If symptoms develop or persist, seek medical attention

Take off all contaminated clothing

Gently blot or brush away excess product

Wash with plenty of lukewarm, gently flowing water

Get medical advice if skin irritation occurs or you feel unwell

Following eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes

If symptoms develop or persist, seek medical attention

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open

Remove contact lenses, if present and easy to do so

Continue rinsing for 15-20 minutes

Get medical advice if eye irritation persists

Following ingestion:

Rinse mouth thoroughly

Seek medical attention if irritation, discomfort, or vomiting persists

4.2 Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Not determined or not available.

Delayed symptoms and effects:

Not determined or not available.

4.3 Indication of any immediate medical attention and special treatment needed

Specific treatment:

Not determined or not available.

Notes for the doctor:

Not determined or not available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition.

Unsuitable extinguishing media:

Not determined or not applicable.

5.2 Special hazards arising from the substance or mixture:

Thermal decomposition can lead to release of irritating gases and vapors.

5.3 Advice for firefighters

Personal protection equipment:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

Special precautions:

Carbon monoxide and carbon dioxide may form upon combustion.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 4 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Heating causes a rise in pressure, risk of bursting and combustion.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation.
Ensure air handling systems are operational.
Wear protective eye wear, gloves and clothing.

6.2 Environmental precautions:

Should not be released into the environment.
Prevent from reaching drains, sewer or waterway.

6.3 Methods and material for containment and cleaning up:

Wear protective eye wear, gloves and clothing.
Sweep or scoop up solid material while minimizing dust generation.
Dispose of contents / container in accordance with local regulations.

6.4 Reference to other sections:

Not determined or not applicable.

SECTION 7: Handling and storage

7.1 Precautions for safe handling:

Use only with adequate ventilation.
Avoid breathing dust.
Do not eat, drink, smoke or use personal products when handling chemical substances.

7.2 Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed.
Keep container dry.
Store in a cool, well-ventilated area.

7.3 Specific end use(s):

Not determined or not applicable.

SECTION 8: Exposure controls/personal protection



8.1 Control parameters

Only those substances with limit values have been included below.

Occupational Exposure limit values:

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Bulgaria	Powder	65997-17-3	TWA: 6.0 mg/m ³ (inhalable fraction)
	Powder	65997-17-3	TWA: 1.0 fibres/cm ³ (respirable fraction)
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Respirable dust)
	Talc Powder	14807-96-6	TWA: 6.0 mg/m ³ (inhalable fraction)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 5 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Talc Powder	14807-96-6	TWA: 3.0 mg/m ³ (respirable fraction)
Cyprus	Powder	65997-17-3	8-hour TWA: 10 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Talc Powder	14807-96-6	8-hour TWA: 706 particles/cm ³
Czech Republic	Powder	65997-17-3	8-hour TWA: 5.0 mg/m ³ (glass laminate dusts)
	Powder	65997-17-3	8-hour TWA: 1.0 fibers/cm ³ (respirable fibers)
	Powder	65997-17-3	8-hour TWA: 4 mg/m ³ (synthetic mineral fibers - all sizes)
	Powder	65997-17-3	8-hour TWA: 1.0 fibers/cm ³ (synthetic mineral respirable fibers)
	Powder	65997-17-3	8-hour TWA: 0.3 fibers/cm ³ (ceramic respirable fibers)
	Talc Powder	14807-96-6	8-hour TWA: 2.0 mg/m ³ (dust, respirable fraction, Fr ≤ 5%)
	Talc Powder	14807-96-6	8-hour TWA: 10 mg/m ³ (dust, respirable fraction, Fr > 5%)
	Talc Powder	14807-96-6	8-hour TWA: 10 mg/m ³ (dust, total concentration)
	Talc Powder	14807-96-6	8-hour TWA: 5.0 mg/m ³ (polymeric material dust)
Croatia	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Total dust) 15-min
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust) 15-min
	Talc Powder	14807-96-6	Maximum (8 hr) allowable concentration: 1 mg/m ³ (respirable dust)
Estonia	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³
	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³ 8-hr
	Talc Powder	14807-96-6	8-hour TWA: 10 mg/m ³ (total dust)
	Talc Powder	14807-96-6	8-hour TWA: 5 mg/m ³ (fine dust)
	Talc Powder	14807-96-6	8-hour TWA: 3 mg/m ³ (plastic)
	Talc Powder	14807-96-6	8-hour TWA: 1 mg/m ³ (textile)
	Talc Powder	14807-96-6	8-hour TWA: 5 mg/m ³ (organic dust, total dust)
Hungary	Powder	65997-17-3	8-Hour TWA (ÁK Value): 1.0 fibers/cm ³
	Talc Powder	14807-96-6	8-hour TWA (ÁK Value): 2 mg/m ³ (respirable)
	Talc Powder	14807-96-6	8-hour TWA (ÁK Value): 10 mg/m ³ (total, inhalable)
Latvia	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour TWA: 2 mg/m ³
	Talc Powder	14807-96-6	8-hour TWA: 4 mg/m ³ (tuff, pumice, perlite)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 6 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (natural and synthetic)
	Talc Powder	14807-96-6	8-hour TWA: 5 mg/m ³ (polymers)
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (abrasive dusts)
	Talc Powder	14807-96-6	8-hour TWA: 4 mg/m ³ (tal-like dust)
Lithuania	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³ (glass fiber)
	Powder	65997-17-3	8-hour TWA: 0.2 fibers/cm ³ (synthetic inorganic, crystal fibers)
	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³ (synthetic inorganic, amorphous fibers)
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (inhalable fraction)
	Talc Powder	14807-96-6	8-hour TWA: 1 mg/m ³ (respirable fraction)
Poland	Titanium Dioxide	13463-67-7	OEL: TWA (NDS) 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour TWA(NDS): 2.0 mg/m ³ (inhalable fraction)
	Powder	65997-17-3	8-hour TWA (NDS): 1.0 fibers/cm ³ (respirable fibers)
	Talc Powder	14807-96-6	8-hour TWA (NDS): 4 mg/m ³ (inhalable fraction)
	Talc Powder	14807-96-6	8-hour TWA (NDS): 1 mg/m ³ (respirable fraction)
Romania	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Titanium Dioxide	13463-67-7	OEL: STEL 15 mg/m ³ 15-min
	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³ (glass wool fibers - respirable fraction)
	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³ (rock wool fibers - respirable fraction)
	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³ (slag wool fibers - respirable fraction)
	Powder	65997-17-3	8-hour TWA: 1 fibers/cm ³ (special purpose glass fibers - respirable fraction)
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (inhalable fraction)
Slovakia	Titanium Dioxide	13463-67-7	OEL: TWA (NPEL) 5 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour TWA (NPEL): 2 fibers/cm ³ (4 mg/m ³)
	Talc Powder	14807-96-6	8-hour TWA (NPEL): 2 mg/m ³ (respirable fraction, Fr ≤ 5%)
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (respirable fraction, Fr > 5%)
Austria	Titanium Dioxide	13463-67-7	OEL: TWA 5 mg/m ³
	Titanium Dioxide	13463-67-7	OEL: STEL 10 mg/m ³

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 7 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Country (Legal Basis)	Substance	Identifier	Permissible concentration
Belgium	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour TWA: 10 mg/m ³ (glass - fibers or dusts of)
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³
	Talc Powder	14807-96-6	8-hour TWA: 10 mg/m ³ (inhalable fraction)
	Talc Powder	14807-96-6	8-hour TWA: 3 mg/m ³ (respirable fraction)
Denmark	Titanium Dioxide	13463-67-7	OEL: TWA 6.0 mg/m ³
	Powder	65997-17-3	TWA: 1 fibers/cm ³
Finland	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour limit: 5 mg/m ³
	Talc Powder	14807-96-6	15-minute limit: 2 ppm (inhalable)
	Talc Powder	14807-96-6	15-minute limit: 1 ppm (respirable)
France	Titanium Dioxide	13463-67-7	OEL: (VME) 10 mg/m ³
	Talc Powder	14807-96-6	Time weighted average (VME): 10 mg/m ³ (inhalable fraction)
	Talc Powder	14807-96-6	Time weighted average (VME): 5 mg/m ³ (respirable fraction)
Greece	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Inhalable) 8-hr
	Titanium Dioxide	13463-67-7	OEL: TWA 5.0 mg/m ³ (Respirable dust) 8-hr
	Talc Powder	14807-96-6	8-hour TWA: 10 mg/m ³ (inhalable)
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (respirable)
Slovenia	Powder	65997-17-3	8-hour TWA: 500000 fibers/m ³
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (Respirable fraction)
Ireland	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Inhalable dust) 8-hr
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust) 8-hr
	Powder	65997-17-3	8-hour OEL (TWA): 2 fibers/cm ³ of air (5 mg/m ³)
	Talc Powder	14807-96-6	8-hour OEL (TWA): 10 mg/m ³ (total inhalable dust)
	Talc Powder	14807-96-6	8-hour OEL (TWA): 0.8 mg/m ³ (respirable fraction)
Italy	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour TWA: 1 fibres/cm ³
	Talc Powder	14807-96-6	8-hour TWA: 2 mg/m ³ (respirable fraction)
Portugal	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	NP 1796-2007 8-hour exposure limit: 1 fibres/cm ³

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 8 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Country (Legal Basis)	Substance	Identifier	Permissible concentration
	Talc Powder	14807-96-6	NP 1796-2007 8-hour exposure limit: 2 mg/m ³ (respirable fraction)
Netherlands	Powder	65997-17-3	Binding 8-hour TWA: 0.5 fibre/cm ³
	Talc Powder	14807-96-6	8-hour TWA: 0.25 mg/m ³ (respirable)
Spain	Titanium Dioxide	13463-67-7	OEL: (VLA_ED) 10.0 mg/m ³ 8-hr
	Powder	65997-17-3	8-hour daily exposure limit (VLA_ED): 0.5 fibres/cm ³
	Talc Powder	14807-96-6	8-hour daily exposure limit (VLA_ED): 2 mg/m ³ (respirable fraction)
Sweden	Titanium Dioxide	13463-67-7	OEL: (NGV) 5.0 (Total dust) mg/m ³
	Powder	65997-17-3	Level Limit Value (NGV): 1 fiber/mL
	Talc Powder	14807-96-6	Level Limit Value (NGV): 2 mg/m ³ (total dust)
	Talc Powder	14807-96-6	Level Limit Value (NGV): 1 mg/m ³ (respirable dust)
United Kingdom	Titanium Dioxide	13463-67-7	OEL: TWA 10.0 mg/m ³ (Total dust)
	Titanium Dioxide	13463-67-7	OEL: TWA 4.0 mg/m ³ (Respirable dust)
	Powder	65997-17-3	TWA: 1 fibre/mL (5 mg/m ³)
	Talc Powder	14807-96-6	TWA: 1 mg/m ³ (respirable dust)
Germany	Talc Powder	14807-96-6	AGW Limit value: 1.25 mg/m ³ (respirable fraction)
	Talc Powder	14807-96-6	AGW limit value: 10 mg/m ³ (inhalable fraction)
	Talc Powder	14807-96-6	AGW Short term (15 min) exposure limit: 20 mg/m ³ (inhalable fraction)

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Derived No Effect Level (DNEL):

Not determined or not applicable.

Predicted No Effect Concentration (PNEC):

Not determined or not applicable.

Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls
Biological monitoring may also be appropriate for some substances

8.2 Exposure controls

Appropriate engineering controls:

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 9 of 14

Epoxy Putty Stick - Under Water Cure - Part A

above.

Personal protection equipment

Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

Respiratory protection:

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

General hygienic measures:

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and at the end of work.

Wash contaminated clothing before reuse.

Environmental exposure controls:

Select controls based on a risk assessment of local conditions.

See section 6 for information on accidental release measures.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Very thick white paste (solid)
Odor	Not available
Odor threshold	Not available
pH	Not available
Melting point/freezing point	Not available
Initial boiling point/range	Not available
Flash point (closed cup)	135°C (275°F)
Evaporation rate	Not available
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	Not available
Vapor density	Not available
Density	1.98
Relative density	Not available
Solubilities	Not determined or not available.
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	Not available
Dynamic viscosity	Not available
Kinematic viscosity	Not available
Explosive properties	Not available
Oxidizing properties	Not available

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity:

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 10 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Does not react under normal conditions of use and storage.

10.2 Chemical stability:

Stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions:

None under normal conditions of use and storage.

10.4 Conditions to avoid:

None known.

10.5 Incompatible materials:

None known.

10.6 Hazardous decomposition products:

None known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Skin corrosion/irritation

Assessment: Causes skin irritation

Product data:

No data available.

Substance data:

Name	Result
Epoxy resin	Causes skin irritation.
Diluent	Causes skin irritation

Serious eye damage/irritation

Assessment: Causes serious eye irritation

Product data:

No data available.

Substance data:

Name	Result
Epoxy resin	Causes serious eye irritation.
Diluent	Causes serious eye damage

Respiratory or skin sensitization

Assessment: May cause an allergic skin reaction

Product data:

No data available.

Substance data:

Name	Result
Epoxy resin	May cause an allergic skin reaction.
Diluent	Result : May cause sensitisation by skin contact.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 11 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Substance data:

Name	Species	Result
Powder	Not applicable	May cause cancer via inhalation.
Titanium Dioxide	Not applicable.	Airborne, unbound particles of respirable size are known to cause cancer.

International Agency for Research on Cancer (IARC):

Name	Classification
Talc Powder	Group 3 - Not classifiable as to its carcinogenicity to humans
Powder	Group 2B
Titanium Dioxide	Group 2B

National Toxicology Program (NTP):

Name	Classification
Powder	Reasonably anticipated to be human carcinogens

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Reproductive Toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Acute (short-term) toxicity

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 12 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Epoxy resin	EC50 - Scenedesmus capricornutum - 9 mg/L - 48 h

Chronic (long-term) toxicity

Product data: No data available.

Substance data: No data available.

12.2 Persistence and degradability

Product data: No data available.

Substance data: No data available.

12.3 Bioaccumulative potential

Product data: No data available.

Substance data: No data available.

12.4 Mobility in soil

Product data: No data available.

Substance data: No data available.

12.5 Results of PBT and vPvB assessment

PBT assessment: This product does not contain any substances that are assessed to be a PBT.

vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

12.6 Other adverse effects: No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Relevant information:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities

SECTION 14: Transport information

International Carriage of Dangerous Goods by Road/Rail (ADR/RID)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Carriage of Dangerous Goods by Inland Waterways (ADN)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Maritime Dangerous Goods (IMDG)

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 13 of 14

Epoxy Putty Stick - Under Water Cure - Part A

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not Regulated
UN proper shipping name	Not Regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

European regulations

Inventory listing (EINECS):

25068-38-6	Epoxy resin	Listed
3101-60-8	Diluent	Listed
14807-96-6	Talc Powder	Listed
37244-96-5	Powder	Not Listed
65997-17-3	Powder	Listed
67762-90-7	Powder additive	Not Listed
13463-67-7	Titanium Dioxide	Listed

REACH SVHC candidate list: Not determined.

REACH SVHC Authorizations: Not determined.

REACH Restriction: Not determined.

Water hazard class (WGK) (Product): Not determined.

Water hazard class (WGK) (Substance):

Ingredient Name	CAS	Class
Epoxy resin	25068-38-6	2
Talc Powder	14807-96-6	Non-hazardous to water.
Powder additive	67762-90-7	Non-hazardous to water.
Titanium Dioxide	13463-67-7	Non-hazardous to water.

Other regulations

Germany MAK: 8-hour TWA: 0.3 mg/m³ (respirable fraction), 8-hour TWA: 4 mg/m³ (inhalable fraction)

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Safety Data Sheet

According to Regulation (EC) No. 1272/2008 (CLP) and (EC) No. 1907/2006 (REACH)

Initial preparation date: 07.24.2018

Page 14 of 14

Epoxy Putty Stick - Under Water Cure - Part A

Indication of changes:

Not applicable.

Abbreviations and Acronyms: None

Classification procedure:

Classification according to Regulation (EC) No. 1272/2008 (CLP)	Method Used
Eye irritation, category 2A	Calculation method
Skin irritation, category 2	Calculation method
Skin sensitization, category 1	Calculation method
Chronic aquatic hazard, category 2	Calculation method

Summary of classification in section 3:

Carc. 1B; H350	Carcinogenicity, category 1B
Skin Sens. 1; H317	Skin sensitization, category 1
Skin Irrit. 2 ; H315	Skin irritation, category 2
Eye Irrit. 2; H319	Eye irritation, category 2A
Aquatic Chronic 2; H411	Chronic aquatic hazard, category 2

Summary of hazard statements in section 3:

H350	May cause cancer
H317	May cause an allergic skin reaction
H315	Causes skin irritation
H319	Causes serious eye irritation
H411	Toxic to aquatic life with long lasting effects

Disclaimer:

This product has been classified in accordance with EC No. 1272/2008 (CLP) and EC No. 1907/2006 (REACH). The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

NFPA: 2-0-0

HMIS: 2-0-0

Initial preparation date: 07.24.2018

End of Safety Data Sheet