

SAFETY DATA SHEET

REF: PR/11ASTD/RPR/M/13397

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product name: PAINT RENOVATOR
Supplier: AUTOGLYM, Works Road, Letchworth, England SG6 1LU
Emergency telephone number: 44 (0) 1462 677766
Identification of the preparation: emulsion
Product use: abrasive polish

2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Class	Weight %
Aliphatic hydrocarbon solvent (<1% aromatics)	64742-48-9	Xn; R65 R10	5 - 20
Calcined alumina	1344-28-1		20 - 50
Mineral oil	8042-47-5		1 - 5

3. HAZARDS IDENTIFICATION

Inhalation: May cause irritation of respiratory tract, Anaesthetic in high concentrations, may cause drowsiness, dizziness and affect the central nervous system.
Skin contact: May irritate. May cause dermatitis.
Eye contact: May irritate.
Ingestion: Liquid aspirated into lungs may cause bronchopneumonia or pulmonary oedema.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. Obtain medical attention.
Skin contact: Wash off with soap and water. Remove and wash contaminated clothing before re-use.
Eye contact: Flush with plenty of water. If eye irritation persists, consult a specialist.
Ingestion: Do not induce vomiting. Consult a physician.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media: foam, carbon dioxide (CO₂), dry chemical

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: Prevent product from entering drains
Methods for cleaning up: Remove all sources of ignition. Soak up with inert absorbent material. Ensure conformity to local disposal regulations.

7. HANDLING AND STORAGE

Handling: Do not breathe vapours/dust. Avoid contact with the skin and the eyes.
Storage: Keep away from sources of ignition - No smoking

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name: UK National occupational exposure limits:
Aliphatic hydrocarbon solvent (<1% aromatics) LTEL= 1000mg/m³, Sol.
Calcined alumina LTEL=10mg/m³ (TD), 5mg/m³ (RD)
Mineral oil LTEL=5mg/m³ AOM
Engineering measures: Ensure adequate ventilation, especially in confined areas.
Personal protection equipment:
Respiratory protection: Wear dust mask if necessary
Hand protection: PVC or other plastic material gloves

9. PHYSICAL AND CHEMICAL PROPERTIES

Form: cream	Boiling point/range:	°C	Flash point: approx 41	°C
Colour: white	Density	1.09 - 1.125	Water solubility	immiscible

10. STABILITY AND REACTIVITY

Stability: Stable

PAINT RENOVATOR

Materials to avoid: oxidizing agents & halogenated compounds

11. TOXICOLOGICAL INFORMATION

Solvent: :LD50/oral/rat = > 5 g/kg, LD50/dermal/rabbit = > 3 g/kg.

12. ECOLOGICAL INFORMATION

Solvent: likely to bioaccumulate but with short retention of the order of a week or less. readily biodegradable.

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products Ensure conformity to local disposal regulations
:

14. TRANSPORT INFORMATION

Conveyance classification: Not classified as dangerous in the meaning of transport regulations.

15. REGULATORY INFORMATION

Classification according to European directive on classification of hazardous preparations 90/492/EEC

Contains: Petroleum distillates

S-phrases(s): S2 - Keep out of reach of children. S62 - If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label

16. OTHER INFORMATION

Last revision dated: 17/07/1997

Further information: .

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.