Mobil Ancillaries

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

	•
1.1. Product identifier	
Trade name or designation of the mixture	Mobil Brake Fluid DOT 4
Registration number	-
Synonyms	None.
Product code	150906, 150904, 150905, 144157
Issue date	18-October-2017
Version number	11
Revision date	02-November-2018
Supersedes date	28-September-2018
1.2. Relevant identified uses of	the substance or mixture and uses advised against
Identified uses	Brake fluid
Uses advised against	None known.
1.3. Details of the supplier of the	e safety data sheet
	Manufactured by Moove Lubricants
Address	Dering Way, Gravesend, Kent DA12 2QX
Telephone	+44 (0) 1474 564 311
Email	technical@uk.moovelub.com
1.4. Emergency telephone	
Asia Pacific	+ (1) 760 476 3960
China	+ (86) 4001 2001 74
Europe	+ (44) 8 08 189 0979
Middle East/Africa	+ (1) 760 476 3959
Access code	334498

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards		
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye

 Hazard summary
 Causes serious eye irritation. Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms



Signal word	Warning
Hazard statements	
H319	Causes serious eye irritation.
Precautionary statements	
Prevention	
P264	Wash thoroughly after handling.
P280	Wear eye protection/face protection.
Response	
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if presen and easy to do. Continue rinsing.

P337 + P313	If eye irritation persists: Get medical advice/attention.
Storage	Store away from incompatible materials.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Supplemental label information	None.
2.3. Other hazards	Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Butyl Triglycol	20 - < 30	143-22-6 205-592-6	-	603-183-00-0	
Classification:	Eye Dam. 1;H318				
Diethylene glycol	5 - < 10	111-46-6 203-872-2	-	603-140-00-6	
Classification:	Acute Tox. 4;H302, ST	OT RE 2;H373			
Butyl Diglycol	1 - < 3	112-34-5 203-961-6	-	603-096-00-8	#
Classification:	Eye Irrit. 2;H319				
Methyl Diglycol	1 - < 3	111-77-3 203-906-6	-	603-107-00-6	#
Classification:	Repr. 2;H361d				

Other components below reportable 70 - < 80 levels

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
4.1. Description of first aid meas	sures
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
4.2. Most important symptoms and effects, both acute and delayed	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
SECTION 5: Firefighting m	neasures
General fire hazards	No unusual fire or explosion hazards noted.
5.1. Extinguishing media Suitable extinguishing media	Alcohol resistant foam. Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear
personnel	appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
For emergency responders	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.
6.2. Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Use water spray to reduce vapours or divert vapour cloud drift.
	Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.
6.4. Reference to other sections	For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.
SECTION 7: Handling and	storage
·	

7.1. Precautions for safe handling	Avoid contact with eyes. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).
7.3. Specific end use(s)	Brake fluid

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Туре	Value	
Butyl Diglycol (CAS 112-34-5)	STEL	101.2 mg/m3	
		15 ppm	
	TWA	67.5 mg/m3	
		10 ppm	
Diethylene glycol (CAS 111-46-6)	TWA	101 mg/m3	
		23 ppm	
Methyl Diglycol (CAS 111-77-3)	TWA	50.1 mg/m3	
		10 ppm	

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU Components Value

Components	гуре	value	
Butyl Diglycol (CAS 112-34-5)	STEL	101.2 mg/m3	
		15 ppm	
	TWA	67.5 mg/m3	
		10 ppm	
Methyl Diglycol (CAS 111-77-3)	TWA	50.1 mg/m3	
		10 ppm	
	No biological exposure limits noted for	the ingradiant(a)	

Recommended monitoring procedures	Follow standard monitoring procedures.	
Derived no effect levels (DNELs)	Not available.	
Predicted no effect concentrations (PNECs)	Not available.	
Exposure guidelines UK EH40 WEL: Skin design	ation	
Methyl Diglycol (CAS 11	1-77-3) Can be absorbed through the skin.	
8.2. Exposure controls		
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.	
Individual protection measures	, such as personal protective equipment	
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.	
Eye/face protection	Wear safety glasses with side shields (or goggles).	
Skin protection		
- Hand protection	Wear appropriate chemical resistant gloves.	
- Other	Wear suitable protective clothing.	
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	
Environmental exposure controls	Environmental manager must be informed of all major releases.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

· · · · · · · · · · · · · · · · · · ·	
Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Yellow-orange.
Odour	Characteristic.
Odour threshold	Not available.
рН	7 - 10.5
Melting point/freezing point	< -50 °C (< -58 °F)
Initial boiling point and boiling range	> 260 °C (> 500 °F)
Flash point	> 100.0 °C (> 212.0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	0.004 hPa estimated
Vapour density	Not available.
Relative density	1.04
Relative density temperature	20 °C (68 °F)
Solubility(ies)	
Solubility (water)	Not available.

Material name: Mobil Brake Fluid DOT 4 - Mobil

150906, 150904, 150905, 144157 Version #: 11 Revision date: 02-November-2018 Issue date: 18-October-2017

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure			
Inhalation	Prolonged inhalation may be harmful.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	Causes serious eye irritation.		
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.		
Symptoms	Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.		

11.1. Information on toxicological effects

Acute toxicity

Components	Species	Test Results
Butyl Diglycol (CAS 112-34	4-5)	
<u>Acute</u>		
Dermal		
LD50	Rabbit	2700 mg/kg
Oral		
LD50	Rat	3306 mg/kg
Butyl Triglycol (CAS 143-2	.2-6)	
Acute		
Dermal		
LD50	Rabbit	3540 mg/kg, 24 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Diethylene glycol (CAS 11	1-46-6)	
Acute		
Dermal		
LD50	Rabbit	11890 mg/kg
Oral		
LD50	Rat	12570 mg/kg
Methyl Diglycol (CAS 111-	77-3)	
Acute		
Dermal		
LD50	Rabbit	6540 mg/kg

Components	Species		Test Results
Oral			
LD50	Rat		5500 mg/kg
Skin corrosion/irritation	Due to parti	al or complete lack of data the classifica	tion is not possible.
Serious eye damage/eye irritation	Causes seri	ous eye irritation.	
Respiratory sensitisation	Due to parti	al or complete lack of data the classifica	tion is not possible.
Skin sensitisation	Due to parti	al or complete lack of data the classifica	tion is not possible.
Germ cell mutagenicity	Due to parti	al or complete lack of data the classifica	tion is not possible.
Carcinogenicity	Due to parti	al or complete lack of data the classifica	tion is not possible.
Reproductive toxicity	This produc	t is not expected to cause reproductive of	or developmental effects.
Specific target organ toxicity - single exposure	Due to parti	al or complete lack of data the classifica	tion is not possible.
Specific target organ toxicity - repeated exposure	Not classifie	Not classified.	
Aspiration hazard	Due to parti	al or complete lack of data the classifica	tion is not possible.
Mixture versus substance information	No informat	No information available.	
Other information	Not availabl	e.	
SECTION 12: Ecological i	nformation		
12.1. Toxicity	Based on av environmen	vailable data, the classification criteria a t.	re not met for hazardous to the aquatic
Product		Species	Test Results
Mobil Brake Fluid DOT 4			
Aquatic			
Fish	LC50	Fish	83169.3672 mg/l, 96 hours estimated
Components		Species	Test Results
Butyl Diglycol (CAS 112-34-5)			
Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	1300 mg/l, 96 hours
Diethylene glycol (CAS 111-46-6) Aquatic)		
Fish	LC50	Western mosquitofish (Gambusia af	finis) > 32000 mg/l, 96 hours
Methyl Diglycol (CAS 111-77-3) Aquatic			
Fish	LC50	Bluegill (Lepomis macrochirus)	7500 mg/l, 96 hours
12.2. Persistence and degradability	No data is a	vailable on the degradability of any ingr	edients in the mixture.
12.3. Bioaccumulative potentia	I		
Partition coefficient n-octanol/water (log Kow) Butyl Diglycol		0.56	
Bioconcentration factor (BCF)	Not availabl		
12.4. Mobility in soil	No data ava	-	
12.5. Results of PBT and vPvB assessment		r vPvB substance or mixture.	
12.6. Other adverse effects			depletion, photochemical ozone creation ntial) are expected from this component.
SECTION 13: Disposal co			
13.1. Waste treatment methods			

13.1. Waste treatment methods Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

EU	waste	code
----	-------	------

The Waste code should be assigned in discussion between the user, the producer and the waste disposal company. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Disposal methods/information

Special precautions

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

ΙΑΤΑ

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Dispose in accordance with all applicable regulations.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.

Not established.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Butyl Diglycol (CAS 112-34-5)

Methyl Diglycol (CAS 112-34-5)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU or	n major accident nazaros involving dangerous substances, as amended
Not listed.	
Other regulations	The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at work, in accordance with Directive 2004/37/EC.
15.2. Chemical safety assessment	No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations References Information on evaluation method leading to the classification of mixture	Not available. Not available. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.
Full text of any H-statements not written out in full under Sections 2 to 15	H302 Harmful if swallowed. H318 Causes serious eye damage. H319 Causes serious eye irritation. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure.
Revision information	Product and Company Identification: Alternate Trade Names
Training information	Follow training instructions when handling this material.
Disclaimer	Mobil cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.