

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier		
Trade name or designation of the mixture	Comma Spray Grease	
Registration number	-	
Synonyms	None.	
Product code	SG500M	
Issue date	20-December-2018	
Version number	03	
Revision date	20-December-2018	
1.2. Relevant identified uses of	the substance or mixture and uses advised against	
Identified uses	Service spray	
Uses advised against	None known.	
1.3. Details of the supplier of the safety data sheet		
	Manufactured by Moove Lubricants	
Address	Dering Way, Gravesend, Kent DA12 2QX	
Telephone	+44 (0) 1474 564 311	
Address	Operations Plant Dering Way, Gravesend, Kent DA12 2QX	
Telephone	+44 (0) 1474 564 311	
Email	technical@uk.moovelub.com	
1.4. Emergency telephone		
Asia Pacific	+ (1) 760 476 3960	
China	+ (86) 4001 2001 74	
Europe	+ (44) 8 08 189 0979	
Middle East/Africa	+ (1) 760 476 3959	
Access code	334498	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards			
Aerosols		Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
Environmental hazards			
Hazardous to the aquatic long-term aquatic hazard	environment,	Category 3	H412 - Harmful to aquatic life with long lasting effects.
Hazard summary	Pressurised cont environment if di	NTS UNDER PRESSURE. tainer may explode when exposed to heat ischarged into watercourses. Not classified posure to the mixture or substance(s) may	for health hazards. However,
2.2. Label elements			
Label according to Regulation (I Hazard pictograms	EC) No. 1272/2008	8 as amended	
Signal word	Danger		
Hazard statements			
H222	Extremely flamm	able aerosol.	

H229	Pressurized container: May burst if heated. Harmful to aquatic life with long lasting effects.
H412	hamini to aquatic me with ong lasting enects.
Precautionary statements	
Prevention	
P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe vapours.
P271	Use only outdoors or in a well-ventilated area.
Response	Not available.
Storage	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Not available.
Supplemental label information	None.
2.3. Other hazards	Not a PBT or vPvB substance or mixture.
SECTION 3: Composition/i	information on ingredients
3.2. Mixtures	
General information	

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
MINERAL OIL (REFINED)	40 - < 50	64742-52-5 265-155-0	-	649-465-00-7	
Classification: Acute Tox. 3	3;H331, Car	с. 1В;Н350			L
Naphtha (petroleum), hydrotreated light	3 - < 5	64742-49-0 265-151-9	01-2119475514-35	649-328-00-1	
Classification: Flam. Liq. 1 3;H336, Aqu	•		rrit. 2;H315, Acute Tox. 3;H3	331, STOT SE	Р

Other components below reportable 50 - < 60 levels

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The full text for all H-statements is displayed in section 16.

Composition comments

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. 4.1. Description of first aid measures Inhalation If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. Eye contact Rinse with water. Get medical attention if irritation develops and persists. Ingestion In the unlikely event of swallowing contact a physician or poison control centre. Exposure may cause temporary irritation, redness, or discomfort. 4.2. Most important symptoms and effects, both acute and delayed 4.3. Indication of any Treat symptomatically. immediate medical attention and special treatment needed **SECTION 5: Firefighting measures** General fire hazards Extremely flammable aerosol.

5.1. Extinguishing media	
Suitable extinguishing media	Powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture	Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Special fire fighting procedures	Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

·····, ····	
For non-emergency personnel	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.
For emergency responders	Keep unnecessary personnel away.
6.2. Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
6.3. Methods and material for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapours or divert vapour cloud drift. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.
	Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
6.4. Reference to other sections	Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any	Level 1 Aerosol.
incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.
7.3. Specific end use(s)	Service spray

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value	
BUTANE (CAS 106-97-8)	STEL	1810 mg/m3	
		750 ppm	
	TWA	1450 mg/m3	
		600 ppm	
iological limit values	No biological exposure limits noted	for the ingredient(s).	
ecommended monitoring ocedures	Follow standard monitoring procedu	ures.	
erived no effect levels NELs)	Not available.		

Predicted no effect concentrations (PNECs)	Not available.
8.2. Exposure controls	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Individual protection measures, s	such as personal protective equipment
General information	Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
- Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
- Other	Wear appropriate chemical resistant clothing.
Respiratory protection	In case of insufficient ventilation, wear suitable respiratory equipment.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

A		
Ap	pear	ance

Appearance	
Physical state	Liquid.
Form	Aerosol
Colour	Yellow Brown.
Odour	Characteristic.
Odour threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	< 0 °C (< 32.0 °F)
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or expl	losive limits
Flammability limit - lower (%)	0.8 %
(/0)	
(70) Flammability limit - upper (%)	9 %
Flammability limit - upper	9 % Not available.
Flammability limit - upper (%)	
Flammability limit - upper (%) Vapour pressure	Not available.
Flammability limit - upper (%) Vapour pressure Vapour density	Not available. Not available.
Flammability limit - upper (%) Vapour pressure Vapour density Relative density	Not available. Not available. 0.7
Flammability limit - upper (%) Vapour pressure Vapour density Relative density Relative density temperature	Not available. Not available. 0.7
Flammability limit - upper (%) Vapour pressure Vapour density Relative density Relative density temperature Solubility(ies)	Not available. Not available. 0.7 20 °C (68 °F)
Flammability limit - upper (%) Vapour pressure Vapour density Relative density Relative density temperature Solubility(ies) Solubility (water) Partition coefficient	Not available. Not available. 0.7 20 °C (68 °F) Not available.
Flammability limit - upper (%) Vapour pressure Vapour density Relative density Relative density temperature Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water)	Not available. Not available. 0.7 20 °C (68 °F) Not available. Not available.
Flammability limit - upper (%) Vapour pressure Vapour density Relative density Relative density temperature Solubility(ies) Solubility(water) Partition coefficient (n-octanol/water) Auto-ignition temperature	Not available. Not available. 0.7 20 °C (68 °F) Not available. Not available. Not available.
Flammability limit - upper (%) Vapour pressure Vapour density Relative density Relative density temperature Solubility(ies) Solubility(ies) Partition coefficient (n-octanol/water) Auto-ignition temperature Decomposition temperature	Not available. Not available. 0.7 20 °C (68 °F) Not available. Not available. Not available. Not available.
Flammability limit - upper (%) Vapour pressure Vapour density Relative density temperature Solubility(ies) Solubility (water) Partition coefficient (n-octanol/water) Auto-ignition temperature Decomposition temperature Viscosity	Not available. Not available. 0.7 20 °C (68 °F) Not available. Not available. Not available. Not available. Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
10.5. Incompatible materials	Strong oxidising agents. Nitrates. Fluorine. Chlorine.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
ymptoms	Exposure may cause temporary irritation, redness, or discomfort.

Symptoms

11.1. Information on toxicological effects

Acute toxicity -

Components	Species	Test Results
MINERAL OIL (REFINED) (CAS 6	•	
Acute	,	
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Rat	> 3.9 mg/l, 4 Hours
Oral		
LD50	Rat	> 2000 mg/kg
Naphtha (petroleum), hydrotreated	d light (CAS 64742-49-0)	
Acute		
Inhalation		
Vapour		
LC50	Rat	> 5.07 mg/l, 4 Hours
* Estimates for product may b	e based on additional component data not shown.	
Skin corrosion/irritation	Based on available data, the classification criteria a	re not met.
Serious eye damage/eye irritation	Due to partial or complete lack of data the classifica	tion is not possible.
Respiratory sensitisation	Due to partial or complete lack of data the classifica	tion is not possible.
Skin sensitisation	Due to partial or complete lack of data the classifica	tion is not possible.
Germ cell mutagenicity	Due to partial or complete lack of data the classifica	tion is not possible.
Carcinogenicity	Due to partial or complete lack of data the classifica	tion is not possible.
Reproductive toxicity	Due to partial or complete lack of data the classifica	tion is not possible.
Specific target organ toxicity - single exposure	Due to partial or complete lack of data the classifica	tion is not possible.
Specific target organ toxicity - repeated exposure	Due to partial or complete lack of data the classifica	tion is not possible.
Aspiration hazard	Due to partial or complete lack of data the classifica	tion is not possible.
Mixture versus substance information	No information available.	
Other information	Not available.	

SECTION 12: Ecological information

12.1. Toxicity		Harmful to aquatic life with long lasting effects. Based on available data, the classification criter are not met for hazardous to the aquatic environment, acute hazard.		
Product		Species	Test Results	
Comma Spray Grease				
Aquatic				
Crustacea	EC50	Daphnia	125 mg/l, 48 hours estimated	
Fish	LC50	Fish	300 mg/l, 96 hours estimated	
Components		Species	Test Results	
Naphtha (petroleum), hydrotrea	ted light (CAS	64742-49-0)		
Aquatic				
Crustacea	EC50	Water flea (Daphnia pulex)	2.7 - 5.1 mg/l, 48 hours	
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss)	8.8 mg/l, 96 hours	
			8.8 mg/l, 96 hours	
* Estimates for product ma	y be based on	additional component data not shown.		
12.2. Persistence and degradability	No data i	s available on the degradability of this pro	duct.	
12.3. Bioaccumulative potent	ial			
Bioconcentration factor (BCF) Not availa	able.		
12.4. Mobility in soil	No data a	No data available.		
12.5. Results of PBT and vPv assessment	B Not a PB	T or vPvB substance or mixture.		
12.6. Other adverse effects		adverse environmental effects (e.g. ozone endocrine disruption, global warming pote	e depletion, photochemical ozone creation ential) are expected from this component.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

UN1950
Aerosols
es)
2
-
2.1
-
D
Not available.
No.
Not available.
UN1950

14.2. UN proper shipping Aerosols name 14.3. Transport hazard class(es) 2 Class Subsidiary risk _ 2.1 Label(s) Not available. 14.4. Packing group 14.5. Environmental hazards No. Not available. 14.6. Special precautions for user ADN UN1950 14.1. UN number 14.2. UN proper shipping Aerosols name 14.3. Transport hazard class(es) 2.1 Class Subsidiary risk 2.1 Label(s) Not available. 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Not available. for user ΙΑΤΑ UN1950 14.1. UN number Aerosols, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk 14.4. Packing group Not available. 14.5. Environmental hazards No. 101 **ERG Code** Not available. 14.6. Special precautions for user Other information Allowed with restrictions. Passenger and cargo aircraft Cargo aircraft only Allowed with restrictions. IMDG 14.1. UN number UN1950 AEROSOLS 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 2 Subsidiary risk 14.4. Packing group Not available. 14.5. Environmental hazards Marine pollutant No. F-D, S-U EmS 14.6. Special precautions Not available. for user Not established. 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.
- Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended MINERAL OIL (REFINED) (CAS 64742-52-5)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

MINERAL OIL (REFINED) (CAS 64742-52-5)

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Other EU regulations

Not listed.

Other regulations	The product is classified and labelled in accordance with EC directives or respective national laws. Pregnant women should not work with the product, if there is the least risk of exposure. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.
National regulations	Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.
15.2. Chemical safety	No Chemical Safety Assessment has been carried out.

assessment

SECTION 16: Other information

List of abbreviations	Not available.
References	Not available.
Information on evaluation method leading to the classification of mixture	The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Revision information Training information Disclaimer H224 Extremely flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H331 Toxic if inhaled.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H411 Toxic to aquatic life with long lasting effects.
Product and Company Identification: Alternate Trade Names
Follow training instructions when handling this material.
Moove Lubricants Itd. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.