



SAFETY DATA SHEET

STP® Diesel Injector Cleaner

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name STP® Diesel Injector Cleaner

Product number 59200

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Fuel additive.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier Energizer Trading Ltd
Sword House
Totteridge Road
High Wycombe
HP13 6DG
UK
Tel: +44 845 602 1995
euregulatory@energizer.com

1.4. Emergency telephone number

Emergency telephone +44 1495 350234
Monday - Thursday: 0830 - 1700
Friday: 0830 - 1530

National emergency telephone number Product information has been submitted to the UK National Poisons Information Service (NPIS) and is accessible to medical health professionals.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Asp. Tox. 1 - H304

Environmental hazards Aquatic Chronic 3 - H412

Human health Pneumonia may be the result if vomited material containing solvents reaches the lungs. The product contains a small amount of sensitising substance. May cause skin sensitisation or allergic reactions in sensitive individuals.

2.2. Label elements

STP® Diesel Injector Cleaner

Hazard pictograms



Signal word

Danger

Hazard statements

EUH208 Contains amides, C18-unsatd., N-[3-(dimethylamine)propyl]. May produce an allergic reaction.
 H304 May be fatal if swallowed and enters airways.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P405 Store locked up.
 P102 Keep out of reach of children.
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
 P331 Do NOT induce vomiting.
 P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

Contains

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	50 - 100%
--	------------------

CAS number: 64742-47-8

EC number: 926-141-6

Classification

Asp. Tox. 1 - H304

2-ethylhexyl nitrate

10 - <25%

CAS number: 27247-96-7

EC number: 248-363-6

UK REACH registration number: UK-01-2930426621-5-XXXX

Classification

Acute Tox. 4 - H302

Acute Tox. 4 - H312

Acute Tox. 4 - H332

Aquatic Chronic 2 - H411

STP® Diesel Injector Cleaner

2-ethylhexan-1-ol		1 - <2.5%
CAS number: 104-76-7	EC number: 203-234-3	UK REACH registration number: UK-01-2180099932-4-XXXX
Classification Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335		
Long-chain alkenyl amido alkyl ammonio acetate		0.25 - <0.5%
CAS number: —	EC number: 947-523-9	
M factor (Acute) = 1		
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Aquatic Acute 1 - H400		
methyl-1H-benzotriazole		0.025 - <0.25%
CAS number: 29385-43-1	EC number: 249-596-6	
Classification Acute Tox. 4 - H302 Repr. 2 - H361d Aquatic Chronic 2 - H411		
amides, C18-unsatd., N-[3-(dimethylamine)propyl]		0.025 - <0.25%
CAS number: —	EC number: 800-353-8	
M factor (Acute) = 1	M factor (Chronic) = 1	
Classification Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1A - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410		

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

Inhalation

If throat irritation or coughing persists, proceed as follows. Remove person to fresh air and keep comfortable for breathing. Get medical attention if symptoms are severe or persist.

STP® Diesel Injector Cleaner

Ingestion	Rinse mouth thoroughly with water. Never give anything by mouth to an unconscious person. Do not induce vomiting unless under the direction of medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if symptoms are severe or persist.
Skin contact	Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at least 15 minutes. Get medical attention if symptoms are severe or persist after washing.
Eye contact	Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms are severe or persist after washing.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Drowsiness. Dizziness.
Ingestion	May cause discomfort if swallowed. Entry into the lungs following ingestion or vomiting may cause chemical pneumonitis.
Skin contact	Prolonged skin contact may cause redness and irritation. May cause skin sensitisation or allergic reactions in sensitive individuals.
Eye contact	May cause irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	Treat symptomatically. Keep affected person under observation.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog. Use fire-extinguishing media suitable for the surrounding fire.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Containers can burst violently or explode when heated, due to excessive pressure build-up.
Hazardous combustion products	Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting	Use water to keep fire exposed containers cool and disperse vapours.
Special protective equipment for firefighters	Use protective equipment appropriate for surrounding materials. Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Firefighter's clothing will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Wear protective clothing as described in Section 8 of this safety data sheet. Eliminate all ignition sources if safe to do so. Avoid contact with skin and eyes.
-----------------------------	--

6.2. Environmental precautions

STP® Diesel Injector Cleaner

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear protective clothing as described in Section 8 of this safety data sheet. No smoking, sparks, flames or other sources of ignition near spillage. Eliminate all ignition sources if safe to do so. Do not touch or walk into spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Use only non-sparking tools. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Reference to other sections See Section 11 for additional information on health hazards. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Wear protective clothing as described in Section 8 of this safety data sheet. Ground/bond container and receiving equipment. Take precautionary measures against static discharges. Keep away from heat, sparks and open flame. Provide adequate ventilation.

Advice on general occupational hygiene Avoid contact with eyes and prolonged skin contact. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in a cool and well-ventilated place. Keep away from heat, sparks and open flame. Take precautionary measures against static discharges.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

2-ethylhexan-1-ol

Long-term exposure limit (8-hour TWA): WEL 1 ppm 5.4 mg/m³

WEL = Workplace Exposure Limit.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (CAS: 64742-47-8)

DNEL Not determined.

PNEC Not determined.

2-ethylhexyl nitrate (CAS: 27247-96-7)

DNEL Workers - Inhalation; Long term systemic effects: 0.35 mg/m³
 Workers - Dermal; Long term systemic effects: 1 mg/kg/day
 Workers - Dermal; Long term local effects: 44 µg/cm²
 General population - Inhalation; Long term systemic effects: 87 µg/m³
 General population - Dermal; Long term systemic effects: 0.52 mg/kg/day
 General population - Dermal; Long term local effects: 22 µg/cm²
 General population - Oral; Long term systemic effects: 0.025 mg/kg/day

STP® Diesel Injector Cleaner

PNEC

Fresh water; 0.0008 mg/l
marine water; 0.00008 mg/l
STP; 10 mg/l
Sediment (Freshwater); 0.00074 mg/kg
Sediment (Marinewater); 0.00074 mg/kg
Soil; 0.000191 mg/kg

2-ethylhexan-1-ol (CAS: 104-76-7)

DNEL

Workers - Inhalation; Long term systemic effects: 12.8 mg/m³
Workers - Inhalation; Long term local effects: 53.2 mg/m³
Workers - Inhalation; Short term local effects: 53.2 mg/m³
Workers - Dermal; Long term systemic effects: 23 mg/kg/day
General population - Inhalation; Long term systemic effects: 2.3 mg/m³
General population - Inhalation; Long term local effects: 26.6 mg/m³
General population - Inhalation; Short term local effects: 26.6 mg/m³
General population - Dermal; Long term systemic effects: 11.4 mg/kg/day
General population - Oral; Long term systemic effects: 1.1 mg/kg/day

PNEC

Fresh water; 0.017 mg/l
Fresh water, Intermittent release; 0.17 mg/l
marine water; 0.002 mg/l
STP; 10 mg/l
Sediment (Freshwater); 0.284 mg/kg
Sediment (Marinewater); 0.028 mg/kg
Soil; 0.047 mg/kg
Oral; 55 mg/kg

Long-chain alkenyl amido alkyl ammonio acetate

DNEL

Workers - Inhalation; Long term systemic effects: 10.6 mg/m³
Workers - Dermal; Long term systemic effects: 3 mg/kg
General population - Inhalation; Long term systemic effects: 2.6 mg/m³
General population - Dermal; Long term systemic effects: 1.5 mg/kg
General population - Oral; Long term systemic effects: 1.5 mg/kg

PNEC

Fresh water; 0.406 µg/l
marine water; 0.0406 µg/l
STP; 10 mg/l
Sediment (Freshwater); 0.501 mg/kg
Sediment (Marinewater); 0.0501 mg/kg
Soil; 0.1 mg/kg

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate ventilation. All handling should only take place in well-ventilated areas. Avoid inhalation of vapours and spray/mists. Use explosion-proof electrical, ventilating and lighting equipment.

STP® Diesel Injector Cleaner

Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Wear tight-fitting, chemical splash goggles or face shield.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended.
Other skin and body protection	Wear appropriate clothing to prevent repeated or prolonged skin contact.
Hygiene measures	Do not smoke in work area. Wash promptly with soap and water if skin becomes contaminated. Wash at the end of each work shift and before eating, smoking and using the toilet.
Respiratory protection	Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'UKCA'-marked.
Environmental exposure controls	Keep container tightly sealed when not in use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid.
Colour	Light (or pale). Amber.
Odour	Characteristic.
Odour threshold	Not determined.
pH	Not determined.
Melting point	Not relevant.
Initial boiling point and range	Not determined.
Flash point	73°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	Not relevant.
Upper/lower flammability or explosive limits	Not relevant.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	0.836 @ 15°C
Bulk density	Not determined.
Partition coefficient	Not determined.
Auto-ignition temperature	Not relevant.
Decomposition Temperature	Not relevant.

STP® Diesel Injector Cleaner

Viscosity	<13.5 cSt @ 40°C
Explosive properties	Not considered to be explosive.
Oxidising properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidising.

9.2. Other information

Other information	No information required.
-------------------	--------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	There are no known reactivity hazards associated with this product.
------------	---

10.2. Chemical stability

Stability	Stable at normal ambient temperatures and when used as recommended.
-----------	---

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Will not polymerise.
------------------------------------	----------------------

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
---------------------	---

10.5. Incompatible materials

Materials to avoid	No specific material or group of materials is likely to react with the product to produce a hazardous situation.
--------------------	--

10.6. Hazardous decomposition products

Hazardous decomposition products	None at ambient temperatures. Thermal decomposition or combustion products may include the following substances: Oxides of carbon. Oxides of nitrogen.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD ₅₀)	Based on available data the classification criteria are not met.
--------------------------------	--

ATE oral (mg/kg)	5,618.96
------------------	----------

Acute toxicity - dermal

Notes (dermal LD ₅₀)	Based on available data the classification criteria are not met.
----------------------------------	--

ATE dermal (mg/kg)	6,438.4
--------------------	---------

Acute toxicity - inhalation

Notes (inhalation LC ₅₀)	Based on available data the classification criteria are not met.
--------------------------------------	--

ATE inhalation (vapours mg/l)	58.91
-------------------------------	-------

Skin corrosion/irritation

Skin corrosion/irritation	Based on available data the classification criteria are not met.
---------------------------	--

Serious eye damage/irritation

Serious eye damage/irritation	Based on available data the classification criteria are not met.
-------------------------------	--

Respiratory sensitisation

Respiratory sensitisation	Based on available data the classification criteria are not met.
---------------------------	--

STP® Diesel Injector Cleaner

Skin sensitisation

Skin sensitisation May cause sensitisation or allergic reactions in sensitive individuals.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Kinematic viscosity $\leq 20.5 \text{ mm}^2/\text{s}$. May be fatal if swallowed and enters airways.

Skin contact

Repeated exposure may cause skin dryness or cracking.

Toxicological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 15,000.0

Species Rat

Notes (oral LD₅₀) REACH dossier information. Read-across data.

ATE oral (mg/kg) 15,000.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Notes (dermal LD₅₀) REACH dossier information. Read-across data.

ATE dermal (mg/kg) 3,160.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 4,951.0

Species Rat

Notes (inhalation LC₅₀) REACH dossier information. Read-across data.

ATE inhalation (vapours mg/l) 4,951.0

STP® Diesel Injector Cleaner

Skin corrosion/irritation

Animal data

Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: Well defined erythema (2). Oedema score: Very slight oedema - barely perceptible (1). REACH dossier information. Read-across data.

Serious eye damage/irritation

Serious eye damage/irritation

Dose: 0.1 ml, 1 second, Rabbit Not irritating. REACH dossier information. Read-across data.

Skin sensitisation

Skin sensitisation

Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information. Read-across data.

Germ cell mutagenicity

Genotoxicity - in vitro

Gene mutation: Negative. REACH dossier information. Read-across data.

Genotoxicity - in vivo

Chromosome aberration: Negative. REACH dossier information. Read-across data.

Carcinogenicity

Carcinogenicity

NOAEC 1100 mg/m³, Inhalation, Mouse REACH dossier information. Read-across data.

Reproductive toxicity

Reproductive toxicity - fertility

Fertility, One-generation study - NOAEL 750 mg/kg/day, Oral, Rat F1 REACH dossier information. Read-across data.

Reproductive toxicity - development

Maternal toxicity: - NOAEL: >= 5220 mg/m³, Inhalation, Rat REACH dossier information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure

NOAEC > 10400 mg/m³, Inhalation, Rat REACH dossier information. Read-across data.

Aspiration hazard

Aspiration hazard

2.4 cSt @ 20°C Asp. Tox. 1 - H304

2-ethylhexyl nitrate

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg)

960.0

Species

Rat

ATE oral (mg/kg)

960.0

Acute toxicity - dermal

ATE dermal (mg/kg)

1,100.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l)

11.0

Skin corrosion/irritation

Animal data

Dose: 0.5 ml, 4 hours, Rabbit Erythema/eschar score: No erythema (0). Oedema score: No oedema (0). REACH dossier information.

STP® Diesel Injector Cleaner

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Not irritating.

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Not sensitising. REACH dossier information.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information.

Reproductive toxicity

Reproductive toxicity - fertility Screening - NOEL 100 mg/kg/day, Oral, Rat F1 REACH dossier information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOEL 500 mg/kg/day, Dermal, Rabbit REACH dossier information.

Aspiration hazard

Aspiration hazard 1.7 mPa s @ 20°C/68°F REACH dossier information.

2-ethylhexan-1-ol

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,290.0

Species Rat

Notes (oral LD₅₀) REACH dossier information.

ATE oral (mg/kg) 3,290.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,000.0

Species Rat

Notes (dermal LD₅₀) REACH dossier information.

ATE dermal (mg/kg) 3,000.0

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 11.0

Skin corrosion/irritation

Animal data Primary dermal irritation index: 6.75 Dose: 0.5 ml, 4 hours, Rabbit REACH dossier information. Highly irritating.

Serious eye damage/irritation

Serious eye damage/irritation Dose: 0.1 ml, 1 second, Rabbit REACH dossier information. Irritating.

Germ cell mutagenicity

Genotoxicity - in vitro Gene mutation: Negative. REACH dossier information.

STP® Diesel Injector Cleaner

Carcinogenicity

Carcinogenicity NOAEL 500 mg/kg/day, Oral, Rat REACH dossier information.

Reproductive toxicity

Reproductive toxicity - development Developmental toxicity: - NOAEL: 2520 mg/kg/day, Dermal, Rat REACH dossier information.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure NOAEL 250 mg/kg/day, Oral, Rat REACH dossier information.

Aspiration hazard

Aspiration hazard 4.3 mPa s @ 40°C/104°F REACH dossier information.

SECTION 12: Ecological information

12.1. Toxicity

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: > 1000 mg/l, Oncorhynchus mykiss (Rainbow trout) REACH dossier information.

Acute toxicity - aquatic invertebrates EL₅₀, 48 hours: > 1000 mg/l, Daphnia magna REACH dossier information.

Acute toxicity - aquatic plants EL₅₀, 72 hours: > 1000 mg/l, Pseudokirchneriella subcapitata REACH dossier information.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOELR, 28 days: 0.173 mg/l, Oncorhynchus mykiss (Rainbow trout) QSAR REACH dossier information.

Chronic toxicity - aquatic invertebrates NOELR, 21 days: 1.22 mg/l, Daphnia magna QSAR REACH dossier information.

2-ethylhexyl nitrate

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 2 mg/l, Brachydanio rerio (Zebra Fish) REACH dossier information.

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: > 12.6 mg/l, Daphnia magna REACH dossier information.

Acute toxicity - aquatic plants EC₅₀, 48 hours: 3.26 mg/l, Pseudokirchneriella subcapitata REACH dossier information.

Acute toxicity - microorganisms EC₅₀, 3 hours: > 1000 mg/l, Activated sludge REACH dossier information.

2-ethylhexan-1-ol

Acute aquatic toxicity

STP® Diesel Injector Cleaner

Acute toxicity - fish	LC ₅₀ , 96 hours: 17.1 mg/l, <i>Leuciscus idus</i> (Golden orfe) REACH dossier information.
Acute toxicity - aquatic invertebrates	EC ₅₀ , 48 hours: 39 mg/l, <i>Daphnia magna</i> REACH dossier information.
Acute toxicity - aquatic plants	EC ₅₀ , 72 hours: 11.5 mg/l, <i>Scenedesmus subspicatus</i> REACH dossier information.

12.2. Persistence and degradability

Persistence and degradability No data available.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradation	Water - Degradation ~ 5%: 3 days Water - Degradation 69: 28 days REACH dossier information. Readily biodegradable but failing the 10-day window.
-----------------------	---

2-ethylhexyl nitrate

Stability (hydrolysis)	pH4 - DT ₅₀ : 1225 minutes @ 50°C/122°F pH7 - DT ₅₀ : 1475 minutes @ 50°C/122°F pH9 - DT ₅₀ : 1702 minutes @ 50°C/122°F REACH dossier information.
Biodegradation	Water - Degradation 0%: 28 days REACH dossier information. No biodegradation observed under test conditions.

2-ethylhexan-1-ol

Biodegradation	Water - Degradation 79 - 99.9%: 2 weeks REACH dossier information. The substance is readily biodegradable.
-----------------------	--

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not determined.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Partition coefficient	Scientifically unjustified. REACH dossier information.
------------------------------	--

2-ethylhexyl nitrate

Partition coefficient	log Pow: 5.24 REACH dossier information.
------------------------------	--

2-ethylhexan-1-ol

Bioaccumulative potential	BCF: 25.33, REACH dossier information.
Partition coefficient	log Pow: 2.9 REACH dossier information.

STP® Diesel Injector Cleaner

12.4. Mobility in soil

Mobility The product is soluble in water.

Ecological information on ingredients.

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

Mobility The product has poor water-solubility.

Surface tension 26.4 mN/m @ 25°C

2-ethylhexyl nitrate

Adsorption/desorption coefficient Water - log Koc: 3.75 @ 22°C/72°F REACH dossier information.

2-ethylhexan-1-ol

Surface tension 47 mN/m @ 20°C/68°F REACH dossier information.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste product or used containers in accordance with local regulations

Disposal methods Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of the local water authority.

SECTION 14: Transport information

General The product is not covered by international regulations on the transport of dangerous goods (IMDG, IATA, ADR/RID).

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

No transport warning sign required.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

STP® Diesel Injector Cleaner

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.
The REACH etc. (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/758 (as amended).
The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2019, SI 2019/720 (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Abbreviations and acronyms used in the safety data sheet ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
RID: European Agreement concerning the International Carriage of Dangerous Goods by Rail.
IMDG: International Maritime Dangerous Goods.
IATA: International Air Transport Association.
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.
ATE: Acute Toxicity Estimate.
DNEL: Derived No Effect Level.
LC50: Lethal Concentration to 50 % of a test population.
LD50: Lethal Dose to 50% of a test population (Median Lethal Dose).
PBT: Persistent, Bioaccumulative and Toxic substance.
vPvB: Very Persistent and Very Bioaccumulative.
BCF: Bioconcentration Factor.

Classification procedures according to SI 2019 No. 720 Asp. Tox. 1 - H304: Calculation method., Expert judgement. Aquatic Chronic 3 - H412: Calculation method. EUH208: Calculation method. EUH066: Expert judgement.

Revision comments Revised formulation. Revised classification.

Revision date 09/08/2022

Revision 16

Supersedes date 18/08/2021

SDS number 106

STP® Diesel Injector Cleaner

Hazard statements in full

H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H361d Suspected of damaging the unborn child.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains amides, C18-unsatd., N-[3-(dimethylamine)propyl]. May produce an allergic reaction.

The information supplied here is accurate to the best knowledge and belief of Energizer Trading Ltd, it is however, not intended as a warranty or representation, and should not be construed as such, for which Energizer Trading Ltd assumes any legal responsibility. Any information or advice obtained from Energizer Trading Ltd other than by means of this publication, and whether relating to Energizer Trading Ltd's products or other materials is also given in good faith. It remains at all times the responsibility of the customer, and user, to ensure that the materials are suitable for the particular purpose intended. Materials not manufactured, or supplied, by Energizer Trading Ltd when used instead of, or in conjunction with materials supplied by Energizer Trading Ltd, it is the customer's responsibility to ensure that all technical, and other information related to such materials is obtained from the manufacturer or supplier. Energizer Trading Ltd accepts no liability for the data contained within this document, as the information herein may be applied under conditions beyond our control, and in situations with which we may be unfamiliar. The information contained within this document is furnished upon condition that the customer and user of this product makes his own determination of the suitability of the product for his particular purpose.