

## SAFETY DATA SHEET

REF: SRP/STD/ODK/6593

### 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**Product name:** SUPER RESIN POLISH  
**Supplier:** AUTOGLYM, Works Road, Letchworth, England SG6 1LU  
**Emergency telephone number:** 44 (0) 1462 677766  
**Identification of the preparation:**  
**Product use:** paint protectant  
**Packing size:** 100, 325 & 500 ml, 1 litre

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Class	Weight %
Aliphatic Hydrocarbon Solvent (<1% aromatics)	64742-48-9	Xn; R65 R10	20 - 50
Aliphatic Hydrocarbon Solvent (<2% aromatics)	64742-47-8	Xn; R65	5 - 10
Anhydrous Aluminium Silicate	66402-68-4		5 - 10

### 3. HAZARDS IDENTIFICATION

**Inhalation:** May cause irritation of respiratory tract. Anaesthetic in high concentrations, may cause drowsiness, dizziness and affect the central nervous system.  
**Skin contact:** May irritate. May cause dermatitis.  
**Eye contact:** May irritate.  
**Ingestion:** Liquid aspirated into lungs may cause bronchopneumonia or pulmonary oedema.

### 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. Obtain medical attention.  
**Skin contact:** Wash off with soap and water. Remove and wash contaminated clothing before re-use.  
**Eye contact:** Flush with plenty of water. Obtain medical attention.  
**Ingestion:** Do not induce vomiting. Call a physician immediately.

### 5. FIRE-FIGHTING MEASURES

**Suitable extinguishing media:** foam, carbon dioxide (CO<sub>2</sub>), dry powder.

### 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Remove all sources of ignition.  
**Environmental precautions:** Do not let product enter drains.  
**Methods for cleaning up:** Soak up with inert absorbent material. Ensure conformity to local disposal regulations.

### 7. HANDLING AND STORAGE

**Handling:** Do not breathe vapours. Avoid contact with skin and eyes.  
**Storage:** Keep away from sources of ignition - No smoking.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<b>Chemical Name:</b>	<b>UK National occupational exposure limits:</b>
Aliphatic Hydrocarbon Solvent (<1% aromatics)	LTEL= 1000mg/m <sup>3</sup> , Sol.
Aliphatic Hydrocarbon Solvent (<2% aromatics)	LTEL= 5mg/m <sup>3</sup> , STEL= 10 mg/m <sup>3</sup> AOM
Anhydrous Aluminium Silicate	LTEL=10mg/m <sup>3</sup> (TD), 5mg/m <sup>3</sup> (RD)

**Engineering measures:** Ensure adequate ventilation.

## SUPER RESIN POLISH

---

**Personal protection equipment:**

**Hand protection:** PVC or other plastic material gloves.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Form:</b> liquid	<b>Boiling point/range:</b>	°C	<b>Flash point:</b> 36 - 61	°C
<b>Colour:</b> white	<b>Density</b>	0.970 - 0.990	<b>Water solubility</b>	immiscible

### 10. STABILITY AND REACTIVITY

**Stability:** Stable

**Materials to avoid:** oxidizing agents & halogenated compounds.

### 11. TOXICOLOGICAL INFORMATION

Solvent: LD50/oral/rat = > 5 g/kg, LD50/dermal/rabbit = > 3 g/kg.

### 12. ECOLOGICAL INFORMATION

Solvent: likely to bioaccumulate but with short retention of the order of a week or less. readily biodegradable.

### 13. DISPOSAL CONSIDERATIONS

**Waste from residues / unused products** Ensure conformity to local disposal regulations.

:

### 14. TRANSPORT INFORMATION

**Conveyance classification:** Not classified as dangerous in the meaning of transport regulations

### 15. REGULATORY INFORMATION

**Classification according to European directive on classification of hazardous preparations 90/492/EEC**

### 16. OTHER INFORMATION

**Last revision dated:** 24/04/1997

**Further information:** .

---

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process unless specified in the text.