SAFETY DATA SHEET



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

Comma Transflow UD 10W40

of the mixture

Registration number

Synonyms None. TFUD*L **Product code**

02-December-2018 Issue date

Version number 09

02-December-2018 **Revision date**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Automotive lubricant

Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Manufactured by Moove Lubricants

Address Dering Way, Gravesend, Kent DA12 2QX

+44 (0) 1474 564 311 **Telephone**

Operations Plant Dering Way, Gravesend, Kent DA12 2QX **Address**

+44 (0) 1474 564 311 **Telephone**

technical@uk.moovelub.com **Email**

1.4. Emergency telephone

+ (1) 760 476 3960 **Asia Pacific** China + (86) 4001 2001 74 Europe + (44) 8 08 189 0979 Middle East/Africa + (1) 760 476 3959

Access code 334498

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

This mixture does not meet the criteria for classification according to Regulation (EC) 1272/2008 as amended.

Not classified for health hazards. However, occupational exposure to the mixture or substance(s) **Hazard summary**

may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms None. None. Signal word

Hazard statements The mixture does not meet the criteria for classification.

Precautionary statements

Prevention Not available. Not available. Response Not available. Storage Disposal Not available.

Supplemental label information

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TFUD*L Version #: 09 Revision date: 02-December-2018 Issue date: 02-December-2018

General information

Chemical name		%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
MINERAL OIL		10 - < 20	Mixture	-	-	#
Classification:	-		-			
CALCIUM LONG CHAIN PHENATE SULFIDE	ALKYL	1 - < 3	122384-87-6 -	01-2119524004-56	-	
Classification:	Aquatic Ch	ronic 4;H413	3			
PHENOL, 4-DODECYL-		< 0.2	104-43-8 203-202-9	-	-	
Classification:	Skin Corr. 1C;H314, Eye Dam. 1;H318, Repr. 1B;H360, Aquatic Acute 1;H400, Aquatic Chronic 1;H410					
Other components below	reportable	80 - < 90				

levels

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

4.2. Most important symptoms

and effects, both acute and delayed

4.3. Indication of any immediate medical attention and special treatment needed Treat symptomatically.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Exposure may cause temporary irritation, redness, or discomfort.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

For emergency responders

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting

procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

personnel

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

Avoid discharge into drains, water courses or onto the ground. 6.2. Environmental precautions

Material name: Comma Transflow UD 10W40 - Moove Lubricants Itd.

TFUD*L Version #: 09 Revision date: 02-December-2018 Issue date: 02-December-2018

6.3. Methods and material for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

6.4. Reference to other

sections

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10

of the SDS).

7.3. Specific end use(s)

Automotive lubricant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components Type Value MINERAL OIL **TWA** 5 mg/m3

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring

procedures

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Personal protection equipment should be chosen according to the CEN standards and in

discussion with the supplier of the personal protective equipment.

Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Wear appropriate chemical resistant gloves. - Hand protection

- Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. Wear appropriate thermal protective clothing, when necessary. Thermal hazards

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

Environmental exposure

controls

Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Liquid. **Form** Liquid. Colour Gold Brown. Odour Slight. Odour threshold Not available.

Material name: Comma Transflow UD 10W40 - Moove Lubricants Itd.

pH Not available.Melting point/freezing point Not available.Initial boiling point and boiling Not available.

range

Flash point > 200.0 °C (> 392.0 °F)

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Vapour pressure0.1 hPa estimatedVapour densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 260 °C (500 °F) estimated

Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot explosive.Oxidising propertiesNot oxidising.

9.2. Other information

Density 0.86 g/cm3

Kinematic viscosity 102 mm²/s (40 °C (104 °F))

Percent volatile 0.12 % estimated

Specific gravity 0.88 estimated

VOC 0.12 % estimated

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

10.4. Conditions to avoidContact with incompatible materials.

10.5. Incompatible materials Strong oxidising agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected.

Eye contact

Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms Exposure may cause temporary irritation, redness, or discomfort.

11.1. Information on toxicological effects

Acute toxicity Not known.

Test Results Components **Species** MINERAL OIL Dermal Liquid LD50 Rabbit > 5000 mg/kg Oral Liquid LD50 Rat > 5000 mg/kg Due to partial or complete lack of data the classification is not possible. Skin corrosion/irritation Serious eye damage/eye Due to partial or complete lack of data the classification is not possible. irritation Respiratory sensitisation Due to partial or complete lack of data the classification is not possible. Skin sensitisation Due to partial or complete lack of data the classification is not possible. Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible. Carcinogenicity Due to partial or complete lack of data the classification is not possible. Reproductive toxicity Due to partial or complete lack of data the classification is not possible. Specific target organ toxicity -Due to partial or complete lack of data the classification is not possible.

single exposure

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity repeated exposure

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

Aspiration hazard

No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic

environment.

Product **Test Results Species**

Comma Transflow UD 10W40

Aquatic

Fish LC50 Fish 121.2121 mg/l, 96 hours estimated

Test Results Components **Species**

PHENOL, 4-DODECYL- (CAS 104-43-8)

Aquatic

LC50 Fish Atlantic salmon (Salmo salar) 0.14 mg/l, 96 hours

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

Partition coefficient

n-octanol/water (log Kow)

6.58 PHENOL, 4-DODECYL-

Not available. **Bioconcentration factor (BCF)**

12.4. Mobility in soil 12.5. Results of PBT and vPvB

assessment

No data available.

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste codeThe Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal methods/information

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Special precautionsDispose in accordance with all applicable regulations.

Not established.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC

Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Not listed

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation

(EC) No 1907/2006, as amended.

National regulations Follow national regulation on the protection of workers from the risks of exposure to carcinogens

and mutagens at work, in accordance with Directive 2004/37/EC.

15.2. Chemical safety

No Chemical Safety Assessment has been carried out.

assessment

Material name: Comma Transflow UD 10W40 - Moove Lubricants Itd.

TFUD*L Version #: 09 Revision date: 02-December-2018 Issue date: 02-December-2018

SECTION 16: Other information

List of abbreviations Not available. References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H314 Causes severe skin burns and eye damage.

H318 Causes serious eye damage.

H360 May damage fertility or the unborn child.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H413 May cause long lasting harmful effects to aquatic life. Product and Company Identification: Alternate Trade Names

Revision information Training information Disclaimer

Follow training instructions when handling this material.

Moove Lubricants ltd. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.