# SAFETY DATA SHEET



# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

of the mixture

Comma White Grease

Registration number

**Synonyms** None. WGR500M **Product code** 

23-December-2018 Issue date

Version number 04

23-December-2018 **Revision date** 

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Service spray Uses advised against None known.

1.3. Details of the supplier of the safety data sheet

Manufactured by Moove Lubricants

Address Dering Way, Gravesend, Kent DA12 2QX

+44 (0) 1474 564 311 **Telephone** 

Operations Plant Dering Way, Gravesend, Kent DA12 2QX **Address** 

+44 (0) 1474 564 311 **Telephone** technical@uk.moovelub.com **Email** 

1.4. Emergency telephone

+ (1) 760 476 3960 **Asia Pacific** China + (86) 4001 2001 74 **Europe** + (44) 8 08 189 0979 Middle East/Africa + (1) 760 476 3959

Access code 334498

#### **SECTION 2: Hazards identification**

#### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

# Classification according to Regulation (EC) No 1272/2008 as amended

**Physical hazards** 

Aerosols Category 1 H222 - Extremely flammable

aerosol.

H229 - Pressurized container: May

burst if heated.

**Health hazards** 

H315 - Causes skin irritation. Skin corrosion/irritation Category 2

Specific target organ toxicity - single Category 3 narcotic effects H336 - May cause drowsiness or exposure

dizziness.

Aspiration hazard H304 - May be fatal if swallowed Category 1

and enters airways.

**Environmental hazards** 

Hazardous to the aquatic environment, Category 2 H411 - Toxic to aquatic life with

long-term aquatic hazard long lasting effects.

Aerosol CONTENTS UNDER PRESSURE. **Hazard summary** 

> Pressurised container may explode when exposed to heat or flame. May cause drowsiness and dizziness. Causes skin irritation. Dangerous for the environment if discharged into watercourses.

Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Hazard pictograms** 



Signal word Danger

**Hazard statements** 

H222 Extremely flammable aerosol.

H229 Pressurized container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Precautionary statements** 

Prevention

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe vapours.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves.

Response Not available.

Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

**2.3. Other hazards**Not a PBT or vPvB substance or mixture.

# **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **General information**

| Chemical name                              | %         | CAS-No. / EC No.        | REACH Registration No.       | Index No.    | Notes |
|--|-----------|-------------------------|------------------------------|--------------|-------|
| Naphtha (petroleum), hydrotreated light    | 40 - < 50 | 64742-49-0<br>265-151-9 | 01-2119475514-35             | 649-328-00-1 |       |
| ligit                                      |           | 200-101-9               |                              |              |       |
| Classification: Flam. Liq. 1<br>3;H336, Aq |           |                         | rrit. 2;H315, Acute Tox. 3;H | 331, STOT SE | Р     |

Other components below reportable 50 - < 60

levels

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

# **SECTION 4: First aid measures**

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth.

Most important symptoms

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

4.2. Most important symptoms and effects, both acute and

redness and pain.

delayed

Material name: Comma White Grease - Moove Lubricants Itd.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

# **SECTION 5: Firefighting measures**

**General fire hazards** Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

Powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

from the substance or mixtur 5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapour. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

For emergency responders

Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections

Not available.

#### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid breathing mist or vapour. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source.

7.3. Specific end use(s) Service spray

# **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

#### Occupational exposure limits

#### **UK. EH40 Workplace Exposure Limits (WELs)**

| Components            | Туре | Value      |  |
|-----------------------|------|------------|--|
| BUTANE (CAS 106-97-8) | STEL | 1810 mg/m3 |  |
|                       |      | 750 ppm    |  |
|                       | TWA  | 1450 mg/m3 |  |
|                       |      | 600 ppm    |  |

**Biological limit values** 

**Recommended monitoring** 

procedures

No biological exposure limits noted for the ingredient(s).

Follow standard monitoring procedures.

Derived no effect levels

(DNELs)

Not available.

Predicted no effect concentrations (PNECs) Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection

Chemical respirator with organic vapour cartridge and full facepiece.

Skin protection Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove - Hand protection

supplier.

Wear appropriate chemical resistant clothing.

Respiratory protection Chemical respirator with organic vapour cartridge and full facepiece.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

**Environmental exposure** 

controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

#### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

**Appearance** 

Liquid. Physical state **Form** Aerosol Colour White.

Characteristic. Odour Not available. **Odour threshold** Not available. Melting point/freezing point Not available. Initial boiling point and boiling Not available.

range

< 0 °C (< 32.0 °F) Flash point Not available. **Evaporation rate** Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Flammability limit - upper 9 %

0.8 %

(%)

Vapour pressureNot available.Vapour densityNot available.

Relative density 0.67

Relative density temperature 20 °C (68 °F)

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.Explosive propertiesNot explosive.Oxidising propertiesNot oxidising.

**9.2. Other information**No relevant additional information available.

## **SECTION 10: Stability and reactivity**

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

**10.4. Conditions to avoid** Avoid temperatures exceeding the flash point. Contact with incompatible materials.

10.5. Incompatible materials10.6. HazardousStrong oxidising agents. Nitrates. Fluorine. Chlorine.No hazardous decomposition products are known.

decomposition products

# **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause drowsiness and dizziness. Headache. Nausea, vomiting. Prolonged inhalation may be

harmful.

**Skin contact** Causes skin irritation.

**Eye contact** Direct contact with eyes may cause temporary irritation.

**Ingestion** May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Symptoms May cause drowsiness and dizziness. Headache. Nausea, vomiting. Skin irritation. May cause

redness and pain.

#### 11.1. Information on toxicological effects

Acute toxicity Narcotic effects.

Components Species Test Results

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Acute Inhalation Vapour

LC50 Rat > 5.07 mg/l, 4 Hours

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation

Due to partial or complete lack of data the classification is not possible.

Skin sensitisation

Due to partial or complete lack of data the classification is not possible.

Germ cell mutagenicity

Due to partial or complete lack of data the classification is not possible.

Carcinogenicity

Due to partial or complete lack of data the classification is not possible.

Reproductive toxicity

Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity - May cause drowsiness and dizziness.

single exposure

in all and a companies and dizziness

Material name: Comma White Grease - Moove Lubricants Itd.

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Specific target organ toxicity -

repeated exposure

Due to partial or complete lack of data the classification is not possible.

Due to partial or complete lack of data the classification is not possible.

Aspiration hazard

Mixture versus substance

information

Other information

No information available.

No information availa

Not available.

# **SECTION 12: Ecological information**

12.1. Toxicity Toxic to aquatic life with long lasting effects. Based on available data, the classification criteria are

not met for hazardous to the aquatic environment, acute hazard.

| Product                   |                     | Species  | Test Results                    |
|---------------------------|---------------------|--|---------------------------------|
| Comma White Grease        |                     |  |                                 |
| Aquatic                   |                     |  |                                 |
| Crustacea                 | EC50                | Daphnia  | 8.3333 mg/l, 48 hours estimated |
| Fish                      | LC50                | Fish   | 20 mg/l, 96 hours estimated     |
| Components                |                     | Species  | Test Results                    |
| Naphtha (petroleum), hydr | otreated light (CAS | 6 64742-49-0)  |                                 |
| Aquatic                   |                     |  |                                 |
| Crustacea                 | EC50                | Water flea (Daphnia pulex)                           | 2.7 - 5.1 mg/l, 48 hours        |
| Fish                      | LC50                | Rainbow trout, donaldson trout (Oncorhynchus mykiss) | 8.8 mg/l, 96 hours              |
|                           |                     |  | 8.8 mg/l, 96 hours              |
|                           |                     |  |                                 |

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

12.2. Persistence and

degradability

No data is available on the degradability of this product.

12.3. Bioaccumulative potential

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil No data available.

12.5. Results of PBT and vPvB

assessment

Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects**No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

# **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

**Residual waste** Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

**EU waste code**The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

**Disposal methods/information** Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Special precautions** Dispose in accordance with all applicable regulations.

#### **SECTION 14: Transport information**

#### **ADR**

**14.1. UN number** UN1950 **14.2. UN proper shipping** Aerosols

name

14.3. Transport hazard class(es)

Class 2
Subsidiary risk Label(s) 2.1
Hazard No. (ADR) -

 $\label{thm:matterial} \mbox{Material name: Comma White Grease - Moove Lubricants Itd.}$ 

Tunnel restriction code D Not available. 14.4. Packing group 14.5. Environmental hazards No. 14.6. Special precautions Not available. for user RID 14.1. UN number UN1950 14.2. UN proper shipping Aerosols 14.3. Transport hazard class(es) Class Subsidiary risk Label(s) 2.1 14.4. Packing group Not available. 14.5. Environmental hazards No. Not available. 14.6. Special precautions for user **ADN** UN1950 14.1. UN number 14.2. UN proper shipping Aerosols 14.3. Transport hazard class(es) **Class** Subsidiary risk 2.1 Label(s) 14.4. Packing group Not available. 14.5. Environmental hazards No. 14.6. Special precautions Not available. for user **IATA** 14.1. UN number UN1950 Aerosols, flammable 14.2. UN proper shipping name 14.3. Transport hazard class(es) Class 2.1 Subsidiary risk Not available. 14.4. Packing group 14.5. Environmental hazards No. **ERG Code** 101 14.6. Special precautions Not available. for user Other information Passenger and cargo Allowed with restrictions. aircraft Cargo aircraft only Allowed with restrictions. **IMDG** UN1950 14.1. UN number **AEROSOLS** 14.2. UN proper shipping name 14.3. Transport hazard class(es) 2 Class Subsidiary risk 14.4. Packing group Not available. 14.5. Environmental hazards Marine pollutant No. F-D, S-U **EmS** 14.6. Special precautions Not available. for user 14.7. Transport in bulk Not established. according to Annex II of MARPOL 73/78 and the IBC

Code



# **SECTION 15: Regulatory information**

# 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

#### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Naphtha (petroleum), hydrotreated light (CAS 64742-49-0)

#### Other EU regulations

# Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations The product is classified and labelled in accordance with EC directives or respective national laws.

Pregnant women should not work with the product, if there is the least risk of exposure. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations** Follow national regulation for work with chemical agents. Young people under 18 years old are not

allowed to work with this product according to EU Directive 94/33/EC on the protection of young

people at work, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

List of abbreviations Not available.

References Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under

Sections 2 to 15 H224 Extremely flammable liquid and vapour.

Material name: Comma White Grease - Moove Lubricants Itd.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H331 Toxic if inhaled.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

**Revision information** Product and Company Identification: Alternate Trade Names

SECTION 2: Hazards identification: Hazard statements

**Training information** 

Disclaimer

Follow training instructions when handling this material.

Moove Lubricants Itd. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in

the sheet was written based on the best knowledge and experience currently available.

Material name: Comma White Grease - Moove Lubricants ltd.