SAFETY DATA SHEET Prestone -40°C Trigger De-icer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name Prestone -40°C Trigger De-icer

Product number PDEI0101A, PDEI0002A, PDEI0005A, PDEI0007A

REACH registration notesThis is a MIXTURE; no registration information contained in this document. Holts are classed

as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Supplier A Holts Car Care Product

Holt Lloyd International Ltd

Barton Dock Road

Stretford Manchester

M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com

Contact person Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs

National emergency telephone https://poisoncentres.echa.europa.eu/

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Flam. Liq. 3 - H226

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Pictogram



Signal word Warning

Hazard statements H226 Flammable liquid and vapour.

Revision date: 05/07/2016 Revision: 1 Supersedes date: 11/09/2013

Prestone -40°C Trigger De-icer

Precautionary statements P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P501 Dispose of contents/ container in accordance with local regulations.

Supplementary precautionary

P233 Keep container tightly closed.

statements P240 Ground and bond

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water or shower.

P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

2.3. Other hazards

The product does not contain any substance that is classified as PBT or vPvB

SECTION 3: Composition/information on ingredients

3.2. Mixtures

ETHANOL 30-60%

CAS number: 64-17-5 EC number: 200-578-6

Classification

Flam. Liq. 2 - H225

ETHANEDIOL 5-10%

CAS number: 107-21-1 EC number: 203-473-3

Classification

Acute Tox. 4 - H302 STOT RE 2 - H373

METHANOL 1-5%

CAS number: 67-56-1 EC number: 200-659-6

Classification

Flam. Liq. 2 - H225 Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 STOT SE 1 - H370

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Revision date: 05/07/2016 Revision: 1 Supersedes date: 11/09/2013

Prestone -40°C Trigger De-icer

Inhalation Move affected person to fresh air at once. Get medical attention. Move affected person to

fresh air and keep warm and at rest in a position comfortable for breathing. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen.

Ingestion Do not induce vomiting. Never give anything by mouth to an unconscious person. Do not

induce vomiting. Remove affected person from source of contamination. Get medical attention immediately. Move affected person to fresh air and keep warm and at rest in a position

comfortable for breathing.

Skin contact Remove affected person from source of contamination. Remove contaminated clothing. Wash

skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after

washing.

Eye contact Remove affected person from source of contamination. Remove any contact lenses and open

eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion May cause nausea, headache, dizziness and intoxication.

Skin contact No specific symptoms known.

Eye contact May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with the following media: Carbon dioxide (CO2). Dry chemicals, sand, dolomite etc.

DO NOT try to put out large fires.

5.2. Special hazards arising from the substance or mixture

Specific hazards Fire creates: Carbon dioxide (CO2). Carbon monoxide (CO). Carbonyl compounds. Oxides of

the following substances: Sulphur.

5.3. Advice for firefighters

Special protective equipment Fi

Firefighters should wear full protective gear including SCBA sets with full face shields.

for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions For personal protection, see Section 8.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots,

clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into

containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. See Section 11 for additional information on health

hazards. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Read and follow manufacturer's recommendations. Avoid spilling. Avoid contact with skin and

eyes.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in

the original container.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

ETHANOL

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1920 mg/m³

Short-term exposure limit (15-minute): WEL

ETHANEDIOL

Long-term exposure limit (8-hour TWA): WEL 20 ppm 52 mg/m³ vapour Short-term exposure limit (15-minute): WEL 40 ppm 104 mg/m³ vapour

Sk

Long-term exposure limit (8-hour TWA): WEL 10 mg/m³ particulate

Sk

METHANOL

Long-term exposure limit (8-hour TWA): WEL 200 ppm 266 mg/m³ Short-term exposure limit (15-minute): WEL 250 ppm 333 mg/m³

Sk

WEL = Workplace Exposure Limit Sk = Can be absorbed through the skin.

ETHANEDIOL (CAS: 107-21-1)

Ingredient comments WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment





SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Clear liquid.

Colour Yellow.

Odour Alcoholic.

Revision date: 05/07/2016 Revision: 1 Supersedes date: 11/09/2013

Prestone -40°C Trigger De-icer

pH pH (concentrated solution): 7.18

Flash point 25°C Closed cup.

Relative density 0.932 @ 20°C

Solubility(ies) Miscible with water.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not polymerise.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Strong acids. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Fire creates: Toxic gases/vapours/fumes of: Carbon monoxide (CO). Carbon dioxide (CO2).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 2,686.98

Acute toxicity - dermal

ATE dermal (mg/kg) 14,150.94

Acute toxicity - inhalation

ATE inhalation (gases ppm) 33,018.87
ATE inhalation (vapours mg/l) 141.51

ATE inhalation (dusts/mists

mg/l)

23.58

Inhalation Harmful by inhalation. May cause respiratory system irritation.

Ingestion Harmful if swallowed.

Skin contact Harmful in contact with skin. Irritating to skin.

Eye contact Irritating to eyes.

Target organs Skin Eyes Respiratory system, lungs

SECTION 12: Ecological information

- 12.1. Toxicity
- 12.2. Persistence and degradability
- 12.3. Bioaccumulative potential
- 12.4. Mobility in soil
- 12.5. Results of PBT and vPvB assessment
- 12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or

watercourses.

Waste class WGK : 2 (Germany)

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 1987 UN No. (IMDG) 1987 UN No. (ICAO) 1987 UN No. (ADN) 1987

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

ALCOHOLS, N.O.S. (CONTAINS ETHANOL, METHANOL)

Proper shipping name (IMDG) ALCOHOLS, N.O.S. (CONTAINS ETHANOL, METHANOL)

Proper shipping name (ICAO) ALCOHOLS, N.O.S. (CONTAINS ETHANOL, METHANOL)

Proper shipping name (ADN) ALCOHOLS, N.O.S. (CONTAINS ETHANOL, METHANOL)

14.3. Transport hazard class(es)

ADR/RID class 3

ADR/RID classification code F1

ADR/RID label 3

IMDG class 3

ICAO class/division 3

ADN class 3

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

ADN packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-E, S-D

ADR transport category 3

Emergency Action Code •3Y

Hazard Identification Number

(ADR/RID)

Tunnel restriction code

(D/E)

30

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations EH40/2005 Workplace exposure limits.

EU legislation Dangerous Substances Directive 67/548/EEC.

Dangerous Preparations Directive 1999/45/EC.

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

Authorisations (Title VII

Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII

Regulation 1907/2006)

No specific restrictions on use are known for this product.

15.2. Chemical safety assessment

SECTION 16: Other information

Revision date 05/07/2016

Revision 1

Supersedes date 11/09/2013

SDS number 14672

Hazard statements in full H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed. H302 Harmful if swallowed. H311 Toxic in contact with skin.

H331 Toxic if inhaled.

H370 Causes damage to organs .

H373 May cause damage to organs (Liver, Kidneys) through prolonged or repeated exposure.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.